



STAINLESS STEEL VACUUM HOPPER LOADERS

SPECIFICATION COMPARISON CHART

**4
MODELS**



MODELS

FEATURES	TAL-15UFX	TAL-6UFX	TAL-12UFX	TAL-3U-EFXDS
LBS Per Hour*	450	660	900	450
Motor H.P.	1.5	1.5	1.5	1.5
Proportional Loading	Available	Available	Available	Available
Filter Blow-Off	Yes	Yes	Yes	Yes
Microprocessor Control	Yes	Yes	Yes	Yes
Remote Control Pad	Yes	Yes	Yes	Yes
Loader Construction	Stainless Steel	Stainless Steel	Stainless Steel	Stainless Steel
Hopper Capacity (polypro)	3.5 lbs.	8.5 lbs.	17 lbs.	4.5 lbs.
Function Lights	Yes	Yes	Yes	Yes
On Demand Cycle Control	Yes	Yes	Yes	Yes
Filter Diameter	7-5/8" O.D.	9-1/2" O.D.	12-1/2" O.D.	7-5/8" O.D.
Filter Material	Reinforced Cloth	Reinforced Cloth	Reinforced Cloth	Reinforced Cloth
Vacuum Hose Grounded	Yes	Yes	Yes	Yes
Hose Length	10 ft.	10 ft.	10 ft.	10 ft.
Probe Part No.	TALP36	TALP36	TALP36	TALP36
Hose/Probe Diameter	1-1/2"	1-1/2"	1-1/2"	1-1/2"
Probe Length	36"	36"	36"	36"
Discharge Hole Dia.	6"	8-1/4"	8-1/4"	2-1/4"
Height above Hopper	22-1/2"	26-3/4"	24-1/2"	28-1/8"
Weight (empty)	25 lbs.	29 lbs.	30-1/2 lbs.	29 lbs.
PRICE	\$745.00	\$895.00	\$1,090.00	\$1,240.00

* Tested with virgin Polypro beads at 10ft vertical and 10ft horizontal transport. Do not use with powders.



**SEE
BEYOND
FOR
PROBES.**



PLASTIC PROCESS EQUIPMENT, INC.

EAST 8303 CORPORATE PARK DRIVE
MACEDONIA, OHIO 44056
216-367-7000 • FAX: 216-367-7022
TOLL FREE: 800-321-0562

WEST 6385 MONTESSOURI STREET
LAS VEGAS, NEVADA 89113
702-433-6385 • FAX: 702-433-6388
TOLL FREE: 800-258-8877

www.ppe.com
e-mail: sales@ppe.com

Toll Free: USA, Canada & Mexico
800-362-0706

Order Fax: 800-223-8305