

# MOLECULAR SIEVE DESICCANT HIGHEST QUALITY – TWO TYPES – TWO SIZES

## **GUARANTEED** TO BE PURE - CLEAN - FRESH MOLECULAR SIEVE DESICCANT

Desiccant dryer manufacturers recommend changing your desiccant tanks or beds periodically to assure optimum performance of your desiccant drying units. How can you tell it's time to change? Longer drying cycles which means more energy consumption to achieve -40°F dew points. Also visually discoloration means replace it.

PPE supplies both types 13X and 4A molecular sieve desiccant in two bead sizes. Due to the various designs of desiccant plastic material dryers, you must replace your bed material with the same type and size that was supplied with your dryer.

Molecular sieve desiccant type 13X has a 12% higher moisture absorption capacity and a larger pore size than type 4A. The larger pores allow it to absorb moisture faster and also absorb larger molecules of moisture as well. Depending on the quantity and type of molecules present, these could react on the surface of the 13X during regeneration and not come off, thus reducing its capacity to function over time. Type 13X is more subject to contamination which in time renders it ineffective.

Because of type 4A's smaller pore size, it is less subject to contamination. However, because of its lower absorbtion capacity and smaller pore openings, the rate at which it absorbs moisture will be lower than with type 13X.

### ••• LOW DUST TYPE •••

FRESH DESICCANT HELPS ACHIEVE LOWER DEW POINTS!



4A 1/8" 4A 1/16" 13X 1/8" 13X 1/16"

#### ALWAYS KEEP YOUR AIR INLET FILTERS CLEAN!

Another factor to consider is the bead size. Small beads (8x12 mesh) have a faster rate of water absorption, but they are more dense and cause a higher pressure drop than the larger (4x8 mesh) beads. Always specify the correct type and size molecular sieve desiccant. If you don't know which type of sieve your dryer was designed to use, contact your dryer manufacturer for their recommendation and then call PPE to place your order.

#### SOLD IN FACTORY-SEALED CONTAINERS TO STAY FRESH AND DRY!

Avoids excess moisture or contamination.

The best drying temperature range for desiccant bead regeneration is 400° to 600°F. Do not exceed 1000°F.

#### IF YOU BLEND SIZES

If the smaller diameter bead size passes through your dryer holding tank screen we suggest you consider installing a stainless steel screen of slightly smaller mesh size in your cannister bottom.

#### **GUARANTEED LOWEST PRICES!**

TYPE 4A DESICCANT

Mix or Match for Quantity Prices

BEAD	MESH SIZE	PART NO.	CONTAINER SIZE	PRICE PER CONTAINER			
SIZE				1 Container		2 or More	
		MS4A4-030	30 lbs.	\$104.50	(\$3.48 lb.)	\$99.50	(\$3.32 lb.)
1/8" Size varies .093 to .185 dia.	4 x 8	MS4A4-110	110 lbs.	\$352.50	(\$3.20 lb.)	\$337.00	(\$3.06 lb.)
		MS4A4-300	300 lbs.	\$893.00	(\$2.98 lb.)	\$855.00	(\$2.85 lb.)
1/16" Size varies .055 to .093 dia.	8 x 12	MS4A8-030	30 lbs.	\$104.50	(\$3.48 lb.)	\$99.50	(\$3.32 lb.)
		MS4A8-110	110 lbs.	\$352.50	(\$3.20 lb.)	\$337.00	(\$3.06 lb.)
		MS4A8-300	300 lbs.	\$893.00	(\$2.98 lb.)	\$855.00	(\$2.85 lb.)

TYPE 13X DESICCANT

SAFETY: Always wear gloves, face mask and safety glasses when handling this product.

BEAD	MESH SIZE	PART NO.	CONTAINER SIZE	PRICE PER CONTAINER			
SIZE				1 CONTAINER		2 OR MORE	
		MS13X4-025	25 lbs.	\$96.50	(\$3.86 lb.)	\$92.00	(\$3.68 lb.)
1/8" Size varies .093 to .185 dia.	4 x 8	MS13X4-110	110 lbs.	\$391.00	(\$3.55 lb.)	\$374.00	(\$3.40 lb.)
		MS13X4-275	275 lbs.	\$908.00	(\$3.30 lb.)	\$870.00	(\$3.16 lb.)
1/16" Size varies .055 to .093 dia.	8 x 12	MS13X8-025	25 lbs.	\$96.50	(\$3.86 lb.)	\$92.00	(\$3.68 lb.)
		MS13X8-110	110 lbs.	\$391.00	(\$3.55 lb.)	\$374.00	(\$3.40 lb.)
		MS13X8-275	275 lbs.	\$908.00	(\$3.30 lb.)	\$870.00	(\$3.16 lb.)



# PLASTIC PROCESS EQUIPMENT, INC.

8303 CORPORATE PARK DRIVE MACEDONIA, OHIO 44056-2300 216-367-7000 • FAX: 216-367-7022 TOLL FREE: 800-321-0562

W 6385 MONTESSOURI STREET E LAS VEGAS, NEVADA 89113-1186 S 702-433-6385 • FAX: 702-433-6388 T TOLL FREE: 800-258-8877 www.ppe.com e-mail: sales@ppe.com

Toll Free: USA, Canada & Mexico 800-362-0706

Order Fax: 800-223-8305