



HONEYCOMB DESICCANT ROTOR DRYERS

THE LATEST HONEYCOMB MATRIX DESICCANT ROTOR WHEEL TECHNOLOGY

**NO PEAKS
AND VALLEYS**

**MAX-DRY® =
CURRENT STATE OF THE ART DRYING**



TYPICAL APPLICATION



STAINLESS STEEL AIR CONE
13-7/8" Long X
7-7/8" O.D. X
2" O.D. Tube
CP-CN1
\$95.00



**RELIABLE
AFFORDABLE
CONTINUOUS DRY AIR**

Drying Rates*

RESIN TYPE	DRYING TEMPERATURE		DRYING TIME HOURS	DRYING RATES LBS. PER HOUR				
	°C	°F		FX-050	FX-100	FX-180	FX-300	FX-400
ABS	80	176	3 - 4	65	132	220	365	485
POM	100	212	2	65	132	230	400	530
PMMA	80	176	2 - 3	65	132	230	385	510
NYLON	75	168	4 - 6	55	110	200	330	440
PC	120	248	3 - 4	55	100	165	285	375
PU	90	194	2 - 3	55	100	165	285	375
PBT	130	267	3 - 4	45	80	132	220	300
PE	90	194	1	45	90	165	265	355
PET	160	320	4 - 6	45	80	132	220	300
PPO	110	230	2	55	100	175	300	400
PP	90	194	1	55	100	175	300	400
PS	80	176	1	65	132	230	400	530
PSU	120	248	3 - 4	55	100	175	300	400
PVC	70	158	1	90	165	300	495	650

* Times and temperatures are general guidelines. Information on specific resins should be obtained from resin suppliers. Maximum drying temperature is 400°F.



PLASTIC PROCESS EQUIPMENT, INC.
EAST 8303 CORPORATE PARK DRIVE
 MACEDONIA, OHIO 44056
 216-367-7000 • FAX: 216-367-7022
 TOLL FREE: 800-321-0562
WEST 6385 MONTESSOURI STREET
 LAS VEGAS, NEVADA 89113
 702-433-6385 • FAX: 702-433-6388
 TOLL FREE: 800-258-8877

www.ppe.com
 e-mail: sales@ppe.com
Toll Free: USA, Canada & Mexico
800-362-0706
 Order Fax: 800-223-8305