

# ETHYLENE GLYCOL TYPES CIRCULATING FLUIDS

#### ETHYLENE GLYCOL PROPERTIES

| %<br>GLYCOL | %<br>WATER | TEMPERATURE<br>RANGE | SPECIFIC HEAT<br>@ 100°F Btu/Lb | SPECIFIC<br>GRAVITY @ 60°F |  |  |  |
|-------------|------------|----------------------|---------------------------------|----------------------------|--|--|--|
| 25%         | 75%        | +10°F to 203°F       | 0.910                           | 1.043                      |  |  |  |
| 30%         | 70%        | +2°F to 204°F        | 0.895                           | 1.049                      |  |  |  |
| 35%         | 65%        | -6°F to 207°F        | 0.872                           | 1.058                      |  |  |  |
| 40%         | 60%        | -13°F to 210°F       | 0.849                           | 1.066                      |  |  |  |
| 45%         | 55%        | -22°F to 212°F       | 0.823                           | 1.074                      |  |  |  |
| 50%         | 50%        | -34°F to 215°F       | 0.797                           | 1.081                      |  |  |  |
| 55%         | 45%        | -48°F to 217°F       | 0.773                           | 1.088                      |  |  |  |
| 60%         | 40%        | -61°F to 220°F       | 0.749                           | 1.094                      |  |  |  |



## ETHYLENE GLYCOL

PPE Ethylene Glycol (EG) Fluid is a colorless, undiluted, practically odorless, low-volatile, hygroscopic liquid that does not contain any foreign additives or inhibitors. EG is completely miscible with water and many organic liquids. EG is the ideal transfer media for use on mold temperature fluid circulators for both heating and chilling applications. EG can be diluted from 1-100% with water. PPE recommends that corrosion inhibitors and pH buffers be added to this product before use. If you are looking for a product already blended, purchase our Inhibited Ethylene Glycol.

**CAUTION:** Do not use automotive anti-freeze as they may contain stop-leak or other additives which will build up on heating elements and cause failures!

| DARTNO   | CONTAINER | QTY PRICES |          |
|----------|-----------|------------|----------|
| PART NO. | SIZE      | 1 - 3      | 4+       |
| EGF05    | 5 GALLON  | \$89.00    | \$84.00  |
| EGF55    | 55 GALLON | \$775.00   | \$735.00 |

5 GALLON GROSS SHIPPING WEIGHT 53 LBS. 55 GALLON GROSS SHIPPING WEIGHT 554 LBS.

#### INHIBITED ETHYLENE GLYCOL

#### with Corrosion Inhibitors & pH Buffers

PPE EGR Ethylene Glycol Fluid is a formulation of undiluted ethylene glycol and a specially designed package of industrial corrosion inhibitors and pH buffers. It is designed specifically to prevent attacks on metals within your systems such as brass, copper, copper alloys, steel, cast iron and aluminum. It also contains no silicates found in automotive antifreeze, which can coat heat exchangers, resulting in reduced heat transfer. PPE recommends a 30% to 40% ethylene glycol solution, unless a lower freezing point is required. Lower than a 30% solution will result in better heat transfer, but will dilute the inhibitors & buffers to an unacceptable level. EGR Ethylene Glycol is dyed bright yellow/green for easy identification and/or leak detection.

| DART NO  | CONTAINER | QTY PRICES |          |
|----------|-----------|------------|----------|
| PART NO. | SIZE      | 1 - 3      | 4+       |
| EGF05R   | 5 GALLON  | \$99.00    | \$93.00  |
| EGF55R   | 55 GALLON | \$875.00   | \$830.00 |

5 GALLON GROSS SHIPPING WEIGHT 53 LBS. 55 GALLON GROSS SHIPPING WEIGHT 554 LBS.



## **GLYCOL TESTERS**


#### **ACCURATELY TEST YOUR GLYCOL CIRCULATING FLUIDS**


#### **HYDROMETER** WITH GLASS BEAKER FOR PROPYLENE & ETHYLENE GLYCOLS

Precision specific gravity hydrometer to accurately check the Glycol to water weight percentage.

Conversion chart included for both Ethylene Glycol and Propylene Glycol.

Part No. EGF101 \$44.00





#### FOR USE ON ETHYLENE GLYCOL ONLY

#### DIAL TYPE GLYCOL TESTER **PROFESSIONAL**

 Precision Calibrated

 Color Coded Indicator Float

**GLYCOL TESTER** 

Acid Resistant

Part No. W1654C \$5.30



8303 CORPORATE PARK DRIVE **MACEDONIA, OHIO 44056-2300** 216-367-7000 • FAX: 216-367-7022

TOLL FREE: 800-321-0562

## ASTIC PROCESS EQUIPMENT, INC.

6385 MONTESSOURI STREET LAS VEGAS, NEVADA 89113-1186 702-433-6385 • FAX: 702-433-6388 TOLL FREE: 800-258-8877

#### www.ppe.com

e-mail: sales@ppe.com

Toll Free: USA, Canada & Mexico 800-362-0706

Order Fax: 800-223-8305

