



# STAINLESS STEEL VACUUM HOPPER LOADERS

## SPECIFICATION COMPARISON CHART

**4  
MODELS**



### MODELS

FEATURES	TAL-15U	TAL-6U	TAL-12U	TAL-3U-E
LBS Per Hour*	450	660	900	450
Motor H.P.	.55	1.5	1.5	.55
Proportional Loading	with Control Unit	with Control Unit	with Control Unit	with Control Unit
Filter Blow-Off	Yes	Yes	Yes	Yes
Microprocessor Control	Yes	Yes	Yes	Yes
Remote Control Box	Yes	Yes	Yes	Yes
Loader Construction	Stainless Steel	Stainless Steel	Stainless Steel	Stainless Steel
Hopper Capacity (polypro)	3.5 lbs.	8.5 lbs.	17 lbs.	4.5 lbs.
Function Lights	Yes	Yes	Yes	Yes
On Demand Cycle Control	Yes	Yes	Yes	Yes
Filter Diameter	7-5/8" O.D.	9-1/2" O.D.	12-1/2" O.D.	7-5/8" O.D.
Filter Material	Reinforced Cloth	Reinforced Cloth	Reinforced Cloth	Reinforced Cloth
Vacuum Hose Grounded	Yes	Yes	Yes	Yes
Hose Length	10 ft.	10 ft.	10 ft.	10 ft.
Probe Part No.	TALP36	TALP36	TALP36	TALP36
Hose/Probe Diameter	1-1/2"	1-1/2"	1-1/2"	1-1/2"
Probe Length	36"	36"	27"	36"
Discharge Hole Dia.	6-1/4"	6-1/4"	8-1/2"	2"
Height above Hopper	20"	23"	25-1/2"	26"
Weight (empty)	22 lbs.	26 lbs.	31 lbs.	24 lbs.
<b>PRICE</b>	<b>\$660.00</b>	<b>\$788.00</b>	<b>\$980.00</b>	<b>\$1035.00</b>

\* Tested with virgin Polypro beads at 10ft vertical and 10ft horizontal transport. Do not use with powders.



**SEE  
BEYOND  
FOR  
PROBES.**



**PLASTIC PROCESS EQUIPMENT, INC.**

6385 Montessouri Street, Las Vegas, Nevada 89113  
702-433-6385 • 800-258-8877 • Fax: 702-433-6388

11218 Challenger Avenue, Odessa, Florida 33556  
727-834-8888 • 800-282-6783 • Fax: 727-834-8873

8303 CORPORATE PARK DRIVE, MACEDONIA (Cleveland), OHIO 44056, USA

216-367-7000 • Toll Free: 800-321-0562 • Fax: 216-367-7022 • Order Fax: 800-223-8305

www.ppe.com • e-mail: sales@ppe.com

Toll Free: USA, Canada & Mexico  
**800-362-0706**