



HONEYCOMB DESICCANT ROTOR DRYERS

THE LATEST HONEYCOMB MATRIX DESICCANT ROTOR WHEEL TECHNOLOGY

**NO PEAKS
AND VALLEYS**

**MAX-DRY® =
CURRENT STATE OF THE ART DRYING**



TYPICAL APPLICATION



RELIABLE - AFFORDABLE - CONTINUOUS DRY AIR

Drying Rates*

Resin Type	Drying Temp. (°F)	Drying Time (Hrs)	MD-30 (Lbs/Hr)	MD-60 (Lbs/Hr)	MD-100 (Lbs/Hr)	MD-150 (Lbs/Hr)	MD-200 (Lbs/Hr)	MD-300 (Lbs/Hr)	MD-400 (Lbs/Hr)
ABS	180 - 200	2 - 3	30	60	100	150	210	340	480
Acrylic	170 - 190	2 - 3	30	60	100	150	210	340	480
Barex	160	6	30	60	100	150	210	340	480
Noryl	175	2 - 3	23	46	80	120	170	290	385
Nylon 6/6	160 - 190	2 - 3	24	48	90	135	190	325	430
Polycarbonate	250	1.5 - 2	24	48	90	135	190	325	430
PET	325 - 375	3 - 4	20	40	75	115	165	260	350
Polysulfone	250 - 275	4 - 5	23	46	80	120	170	290	385
Polyurethane	180 - 200	3 - 4	30	60	110	160	240	380	520
SAN	180	2 - 3	30	60	110	160	240	380	520

* Times and temperatures are general guidelines. Information on specific resins should be obtained from resin suppliers. Maximum drying temperature is 400°F.



PLASTIC PROCESS EQUIPMENT, INC.

www.ppe.com • e-mail: sales@ppe.com

6385 Montessouri Street, Las Vegas, Nevada 89113
702-433-6385 • 800-258-8877 • Fax: 702-433-6388

11218 Challenger Avenue, Odessa, Florida 33556
727-834-8888 • 800-282-6783 • Fax: 727-834-8873

8303 CORPORATE PARK DRIVE, MACEDONIA (Cleveland), OHIO 44056, USA

216-367-7000 • Toll Free: 800-321-0562 • Fax: 216-367-7022 • Order Fax: 800-223-8305

Toll Free: USA, Canada & Mexico
800-362-0706