



# MASTER<sup>®</sup> HEAT GUN

## FOR FAST PORTABLE FLAMELESS HEAT

50<sup>TH</sup>  
ANNIVERSARY

### - USES -

- CLEANING NOZZLES, SCREW TIPS, BARRELS AND SCREWS.
- HEATING NOZZLES AND SCREW TIPS BEFORE REMOVAL.
- REMOVING PLASTIC FROM HEATER BANDS AND OTHER PARTS.
- APPLYING FORM-FIT AND SHRINK TUBING.
- SOFTEN, MOLD, BEND AND FORM PLASTICS.
- BONDING VINYLs AND WELDING OTHER PLASTICS FAST.

**UPGRADED MOTOR  
INCREASED AIRFLOW  
REDESIGNED GRIP**



### SPECIFICATIONS:

- Avg. air velocity - 3,400 FPM at ambient temp.
- Avg. air volume, shutter open - 27 CFM at ambient temp.
- Overall dimensions - 10"L x 5-1/4"W x 9-1/2"H. 1-3/16" dia nozzle.
- Shipping weight 5 lbs.
- Net weight 3-1/2 lbs.
- Temperature: 1,200°F



### MASTER<sup>®</sup> Quality Construction Means Rugged Reliability

The Master<sup>®</sup> Heat Gun is the result of more than 50 years leadership in building rugged, reliable heat guns. It is engineered to deliver the temperatures and air volume required for the most demanding jobs in factories, laboratories and workshops. Every component is designed to meet the exacting demands of heavy duty industrial use. Check the quality features below, and see for yourself why the Master<sup>®</sup> Heat Gun is the overwhelming industry choice in portable, flameless heat tools.

- |   |   |  |
|---|---|--|
| 1. Double-jacketed heater housing protects heating element from damage.                                   | 4. Fixed air intake provides temperature consistency, improving process control.  | 7. Non-slip rubber-backed base permits full 90° rotation of heat gun for use in any position on workbench or assembly line.        |
| 2. Reinforced, quick-change mica-insulated ceramic heating element withstands hard use.                   | 5. Upgraded long-life universal motor delivers 2X Plus run life. Production line quality for high volume heat, hour after hour. | 8. Redesigned ergonomic soft grip handle combined with overall balance of unit gives operator secure grip and firm control of gun. |
| 3. Sturdy die-cast aluminum housing is rugged and light weight. Protects motor assembly from hard knocks. | 6. Three-position "Hot-Cool-Off" fingertip rocker switch is easy to use.  | 9. Heavy duty, all resistant neoprene 3-wire cordset features a molded-on grounded 3-prong plug.                                   |

PART NO.	DESCRIPTION	PRICE
HG-501D	HEAT GUN, 120 VOLTS, 18 AMPS, 750-1000°F TEMPERATURE RANGE	\$139.50
HAS-011K	SPARE HEATING ELEMENT FOR HG-501A	\$22.50
HAS-043K	SPARE HEATING ELEMENT FOR HG-751B & HG-501D	\$22.50
A-160-HG	SHRINK TUBING ATTACHMENT FOR TUBING UP TO 3/4" O.D.	\$21.25
A-170-HG	SHRINK TUBING ATTACHMENT FOR TUBING FROM 3/4" O.D. TO 2" O.D.	\$21.25
51309	1/4" PINPOINT ATTACHMENT	\$21.25
51013	PLASTIC MOLDED CARRYING & STORAGE CASE	\$38.75
BRU-089K	BRUSH KIT: INCLUDES BRUSHES, CAPS & SPRINGS	\$10.50/kit



### PLASTIC PROCESS EQUIPMENT, INC.

8303 CORPORATE PARK DRIVE  
MACEDONIA, OHIO 44056-2300  
216-367-7000 • FAX: 216-367-7022  
TOLL FREE: 800-321-0562

6385 MONTESSOURI STREET  
LAS VEGAS, NEVADA 89113-1186  
702-433-6385 • FAX: 702-433-6388  
TOLL FREE: 800-258-8877

[www.ppe.com](http://www.ppe.com)

e-mail: [sales@ppe.com](mailto:sales@ppe.com)

Toll Free: USA, Canada & Mexico

**800-362-0706**

Order Fax: 800-223-8305