

AIR OPERATED GATE CUTTERS



6-13/16" O.A. Length

Blades

not included.

\$483.50

Weight 2.84 lb. 2-15/16" body dia.

REDUCES OPERATOR FATIGUE - LOWERS YOUR CUTTER COSTS 20 MODELS - LIGHTWEIGHT - USES LOW AIR PRESSURE

AH30W Hand-Held Model

1.058 lbs. Cutting Pressure

0.47" dia. cutting capacity.

6-13/16" O.A. Length Weight 2.58 lb. 2-15/16" body dia.




Model AH30W (old #HS-50F).....

Uses blades: B3015, B3030, B308P, OS-30, OR-30, B3000, B30CTL & A8WP3

Blade opening:

Blade length: 15/16'

Blade angle: 30°



11/16" at tip

1-1/2

15°

15/16" at base

Part No. **B3015** (old #F9P).....\$98.00

15° ROUND BACK BLADES

Blade opening:


Blade length:

Blade angle:

30° ROUND BACK BLADES

9/16" at tip

9/32" at base



Part No. **B3030** (old #FD9P)...\$98.00

FLAT BACK BLADES

AR30W Foot Switch/EOAT Model

Model AR30W (old #HS-50FM)

Uses blades: B3015, B3030, B308P, OS-30, OR-30, B3000, B30CTL & A8WP3

1.058 lbs. Cutting Pressure

71-85 P.S.I. air supply required

(Air hose & Foot Switch not supplied)


0.47" dia. cutting capacity.

Blade opening: 9/32" at tip 9/64" at base

Blade length: 25/32"

0 Blade angle:

*R1/4



Part No. **B308P** (old #FR8P)...\$98.00

CRIMPING BLADES

Blade opening: 7/16" at tip 7/32" at base

> Crimps Wire Sizes: 22-16, 16-14, 12-10






Part No. A8WP3\$109.90

LONG FLAT BACK BLADES Blade opening: 5/8" at tip

5/16" at base

1-7/16" Blade length: Blade angle:



Part No. **B3000** (old #F9PS)...\$105.00

PERPENDICULAR BLADES

Blade opening: 3/8" at tip

n/a" at base Blade length: 5/8'

Blade angle:




No. **B30CTL** (old #FP10F)...\$134.00

OFFSET FLAT BACK BLADES

Blade opening: 9/16" at tip 9/32" at base

Blade length:

Blade angle: 09





Part No. **OS-30**\$215.00

REVERSE OFFSET BLADES

Blade opening: 9/16" at tip 9/32" at base

Blade length: Blade angle: 09





Part No. **OR-30**\$215.00

ALL BLADES

They can be removed for sharpening and can be reversed for left hand operation.

SPECIAL NOTICE

You must install an air line filter, oiler and regulator between your air supply and our power units. Failure to do this will void your factory

FOOT SWITCH

Use with 8mm Push-In Tubing



Part No. HS-88-01 Price \$111.25

FOOT SWITCH

Use with Air Hose P-88-100



Part No. HS-88-00 Price \$104.50

AIR HOSE

39" long with Interchange Couplers and 1 Male Fitting for Gate Cutter

8mm O.D.



Part No. P-88-100

Price \$27.50

SPECIAL NOTICE: You must install an air line filter, oiler and regulator between your air supply and our power units. Failure to do this will void your factory warranty

* R Thread designation for metric threads is the same as B.S.P.T. (British Standard Pipe Threads, Tapered).



8303 CORPORATE PARK DRIVE

MACEDONIA, OHIO 44056-2300 216-367-7000 • FAX: 216-367-7022 **TOLL FREE: 800-321-0562**

ASTIC PROCESS EQUIPMENT, INC.

6385 MONTESSOURI STREET LAS VEGAS, NEVADA 89113-1186 702-433-6385 • FAX: 702-433-6388 TOLL FREE: 800-258-8877

www.ppe.com

e-mail: sales@ppe.com

Toll Free: USA, Canada & Mexico 00-362-0706

Order Fax: 800-223-8305