

MOLD SAFETY STRAP

LOCKS MOLD WHEN NOT IN USE

- Features -

- Keeps the mold closed and locked when not in the press.
- Mold automatically unlocks when mounted on the machine platen.
- High visibility yellow finish makes the safety strap easy to spot and identify if the mold is locked.
- Simplifies storage and transportation of the mold.
- Increase safety by securely locking mold halves together.
- 3 sizes available.

MANUFACTURED IN A QUALITY SYSTEM CERTIFIED FACILITY.



CUMSA


SAFETY STRAP DIMENSIONS 1.125" DOWEL PIN Ø 3/8" x 1 1/4" 1.1811" 1.50 0.4724" Ø 12 mm Ø 0.4724'


1/2" RADIUS

PART NO.	L		М		V°	PRICE
	mm	inches	mm	inches	Χ°	EACH
ML75	75	2.953	100	3.937	12°	\$112.90

APPLICATION & INSTALLATION

BEGIN INSTALLATION BY DRILLING THE THREE HOLES ILLUSTRATED IN DRAWINGS ONE, TWO & THREE. THE DOWEL PIN IN DRAWING ONE SHOULD BE PLACED ON THE PART OF THE MOLD ATTACHED TO THE MOVING PLATEN, WHILE THE STRAP IS MOUNTED ON THE PART OF THE MOLD ATTACHED TO THE STATIONARY PLATEN. THE HOLE IN DRAWING TWO IS FOR THE SAFETY STRAP CATCH SPRING, AND THE HOLE IN DRAWING THREE IS WHERE THE STRAP IS ATTACHED TO THE MOLD.





469 469

<u>1/4</u> - 20 x 1.5"



8303 CORPORATE PARK DRIVE **MACEDONIA, OHIO 44056-2300** 216-367-7000 • FAX: 216-367-7022

TOLL FREE: 800-321-0562

ASTIC PROCESS EQUIPMENT, INC.

6385 MONTESSOURI STREET LAS VEGAS, NEVADA 89113-1186 702-433-6385 • FAX: 702-433-6388

TOLL FREE: 800-258-8877

www.ppe.com

e-mail: sales@ppe.com

Toll Free: USA, Canada & Mexico 300-362-0706

Order Fax: 800-223-8305