



**HEAVY
DUTY**

MACHINE MOUNTING PADS

WITH BUILT-IN LEVEL ADJUSTMENT

100 TO 12,000 LBS. LOADING PER MOUNT

Here's how to select the right PPE Mount:

- 1 Determine weight of machine.
- 2 Divide weight of machine by number of lagging bolt holes to determine maximum load per mount. If load is not distributed evenly, estimate load on each mount.
- 3 Refer to Load Range chart below for correct PPE Mount.

**DEPENDABLE
QUALITY
SUPPORTS
YOUR
MACHINES!**

ALL METAL PARTS
ZINC PLATED
FOR LONG LIFE

LEVELING SCREW
(LONGER SCREWS
AVAILABLE. MUST
BE PURCHASED
AS AN EXTRA.)

LOCKING NUT &
WASHER

HEAVY THEADED
LEVELING PLATE

HEAVY DUTY DRAWN
STEEL SUPPORT PLATE

SNAP RINGS
RETAIN MOUNTS
TO LEVELING
PLATE WHEN
LIFTING MACHINE

EXTRA THICK HIGH DENSITY
VIBRATION DAMPENING
CHLOROPRENE RUBBER
RESISTANT TO OIL AND
WATER

-SPARE PARTS-

PART	SIZE	PART NO.	PRICE
BOLT	M-12X4-3/4"	M12X4	\$5.40
BOLT	M-16X4-3/4"	M16X4	6.45
BOLT	M-20X6-7/8"	M20X6	10.75
BOLT	M-12X8"	M12X8	13.85
BOLT	M-16X8"	M16X8	17.55
BOLT	M-20X10"	M20X10	26.75
LOCK NUT	M-12	M12LN	.50
LOCK NUT	M-16	M16LN	.75
LOCK NUT	M-20	M20LN	1.00
WASHER	M-12	M12W	.25
WASHER	M-16	M16W	.35
WASHER	M-20	M20W	.45

* Models 3A and 5A include a special bushing with M20 to M16 threads and a M16 threaded bolt.

				*Smaller Diameter Bolt	Extra Heavy Duty	Extra Heavy Duty	*Smaller Diameter Bolt
SPECIFICATION/PART#	MODEL-1	MODEL-2	MODEL-3	MODEL-3A	MODEL-4	MODEL-5	MODEL-5A
PRICES 1-8	\$32.50	\$61.50	\$88.75	\$92.50	\$105.40	\$171.25	\$149.00
9 OR MORE	\$31.25	\$59.15	\$85.40	\$89.00	\$101.35	\$164.75	\$143.00
DIAMETER	3-1/8"	4-3/4"	6-5/16"	6-5/16"	6-5/16"	7-7/8"	7-7/8"
HEIGHT, INCL. LEVELING PLATE	1-5/8"	1-15/16"	2-5/16"	2-5/16"	2-5/16"	2-23/32"	2-23/32"
LEVEL ADJUSTMENT	7/8"	7/8"	1"	1"	1"	1"	1"
OVER-ALL HEIGHT	5-1/4"	5-1/4"	7-1/2"	5-1/2"	7-1/2"	7-7/8"	5-7/8"
LEVELING BOLT (METRIC)	M12X1.25mm	M16X1.50mm	M20X1.50mm	M16X1.50mm	M20X1.50mm	M20X1.50mm	M16X1.50mm
LEVELING BOLT LENGTH	4-3/4"	4-3/4"	6-7/8"	4-3/4"	6-11/16"	6-11/16"	4-3/4"
APPROX. SHIPPING WEIGHT	2lbs.	4lbs.	7lbs.	7lbs.	8lbs.	14lbs.	13lbs.
LOAD RANGE PER MOUNT(LBS.) NON-IMPACT MACHINERY	100-1,100	880-2,200	1,760-5,500	1,800-5,500	3,300-8,800	6,600-12,000	3,500-11,000
125 OR LESS STROKES PER MIN.	150-500	500-1,200	1,200-3,850	1,200-3,850	3,520-6,160	5,940-8,800	2,400-7,500
125-160 STROKES PER MIN.	150-350	350-850	1,000-3,000	1,000-3,000	2,090-4,620	4,290-7,700	2,000-6,000
160-200 STROKES PER MIN.	100-275	275-650	700-2,000	700-2,000	1,650-3,080	2,860-5,280	1,300-3,750

1. Above loads are conservative to ensure maximum vibration dampening and noise elimination.

2. PPE Mounts are NOT designed for use on machines that must be fastened to the floor to prevent tipping.

3. Longer leveling screws are available see spare parts.



PLASTIC PROCESS EQUIPMENT, INC.

www.ppe.com • e-mail: sales@ppe.com

PPE WEST 6385 Montessouri Street, Las Vegas, Nevada 89113
702-433-6385 • 800-258-8877 • Fax: 702-433-6388

PPE SOUTH 11218 Challenger Avenue, Odessa, Florida 33556
727-834-8888 • 800-282-6783 • Fax: 727-834-8873

8303 CORPORATE PARK DRIVE, MACEDONIA (Cleveland), OHIO 44056, USA

Toll Free: USA, Canada & Mexico
800-362-0706

216-367-7000 • Toll Free: 800-321-0562 • Fax: 216-367-7022 • Order Fax: 800-223-8305