



**HEAVY
DUTY**

MACHINE MOUNTING PADS

WITH BUILT-IN LEVEL ADJUSTMENT

100 TO 12,000 LBS. LOADING PER MOUNT

Here's how to select the right PPE Mount:

- 1 Determine weight of machine.
- 2 Divide weight of machine by number of lagging bolt holes to determine maximum load per mount. If load is not distributed evenly, estimate load on each mount.
- 3 Refer to Load Range chart below for correct PPE Mount.

**UP TO 1"
HEIGHT
ADJUSTMENT**
**CHECK THE
COMPETITION**

ISO-9001

MANUFACTURED IN A
QUALITY SYSTEM CERTIFIED
FACILITY.

ALL METAL PARTS
ZINC PLATED
FOR LONG LIFE

LEVELING SCREW
(LONGER SCREWS
AVAILABLE. MUST
BE PURCHASED
AS AN EXTRA.)

LOCKING NUT &
WASHER

HEAVY THEADED
LEVELING PLATE

HEAVY DUTY DRAWN
STEEL SUPPORT PLATE

SNAP RINGS
RETAIN MOUNTS
TO LEVELING
PLATE WHEN
LIFTING MACHINE

EXTRA THICK HIGH DENSITY
VIBRATION DAMPENING
CHLOROPRENE RUBBER
RESISTANT TO OIL AND
WATER

-SPARE PARTS-

| PART | SIZE | PART NO. | PRICE |
|----------|-------------|----------|---------|
| BOLT | M-12X4-3/4" | M12X4 | \$5.40 |
| BOLT | M-16X4-3/4" | M16X4 | \$6.45 |
| BOLT | M-20X6-7/8" | M20X6 | \$10.75 |
| BOLT | M-12X8" | M12X8 | \$20.00 |
| BOLT | M-16X8" | M16X8 | \$24.35 |
| BOLT | M-20X10" | M20X10 | \$33.90 |
| LOCK NUT | M-12 | M12LN | \$.50 |
| LOCK NUT | M-16 | M16LN | \$.75 |
| LOCK NUT | M-20 | M20LN | \$1.00 |
| WASHER | M-12 | M12W | \$.25 |
| WASHER | M-16 | M16W | \$.35 |
| WASHER | M-20 | M20W | \$.45 |

* Models 3A and 5A include a special bushing with M20 to M16 threads and a M16 threaded bolt.

| SPECIFICATION/PART# | MODEL-1 | MODEL-2 | MODEL-3 | MODEL-3A | MODEL-4 | MODEL-5 | MODEL-5A |
|--|------------|------------|-------------|-------------|-------------|--------------|--------------|
| PRICES 1-8 | \$42.00 | \$80.60 | \$116.50 | \$117.25 | \$140.00 | \$228.00 | \$218.00 |
| 9 OR MORE | \$40.25 | \$77.25 | \$111.75 | \$112.50 | \$134.00 | \$218.50 | \$208.50 |
| DIAMETER | 3-1/8" | 4-3/4" | 6-5/16" | 6-5/16" | 6-5/16" | 7-7/8" | 7-7/8" |
| HEIGHT, INCL. LEVELING PLATE | 1-5/8" | 1-15/16" | 2-5/16" | 2-5/16" | 2-5/16" | 2-23/32" | 2-23/32" |
| LEVEL ADJUSTMENT | 7/8" | 7/8" | 1" | 1" | 1" | 1" | 1" |
| OVER-ALL HEIGHT | 5-1/4" | 5-1/4" | 7-1/2" | 5-1/2" | 7-1/2" | 7-7/8" | 5-7/8" |
| LEVELING BOLT (METRIC) | M12X1.25mm | M16X1.50mm | M20X1.50mm | M16X1.50mm | M20X1.50mm | M20X1.50mm | M16X1.50mm |
| LEVELING BOLT LENGTH | 4-3/4" | 4-3/4" | 6-7/8" | 4-3/4" | 6-11/16" | 6-11/16" | 4-3/4" |
| APPROX. SHIPPING WEIGHT | 2lbs. | 4lbs. | 7lbs. | 7lbs. | 8lbs. | 14lbs. | 13lbs. |
| LOAD RANGE PER MOUNT(LBS.) NON-IMPACT MACHINERY | 100-1,100 | 880-2,200 | 1,760-5,500 | 1,800-5,500 | 3,300-8,800 | 6,600-12,000 | 3,500-11,000 |
| 125 OR LESS STROKES PER MIN. | 150-500 | 500-1,200 | 1,200-3,850 | 1,200-3,850 | 3,520-6,160 | 5,940-8,800 | 2,400-7,500 |
| 125-160 STROKES PER MIN. | 150-350 | 350-850 | 1,000-3,000 | 1,000-3,000 | 2,090-4,620 | 4,290-7,700 | 2,000-6,000 |
| 160-200 STROKES PER MIN. | 100-275 | 275-650 | 700-2,000 | 700-2,000 | 1,650-3,080 | 2,860-5,280 | 1,300-3,750 |

1. Above loads are conservative to ensure maximum vibration dampening and noise elimination.

2. PPE Mounts are NOT designed for use on machines that must be fastened to the floor to prevent tipping.

3. Longer leveling screws are available see spare parts.



PLASTIC PROCESS EQUIPMENT, INC.

8303 CORPORATE PARK DRIVE
MACEDONIA, OHIO 44056
216-367-7000 • FAX: 216-367-7022
TOLL FREE: 800-321-0562

6385 MONTESSOURI STREET
LAS VEGAS, NEVADA 89113
702-433-6385 • FAX: 702-433-6388
TOLL FREE: 800-258-8877

www.ppe.com
e-mail: sales@ppe.com

Toll Free: USA, Canada & Mexico
800-362-0706

Order Fax: 800-223-8305