



GENERAL SERVICE HOSE

FOR USE WITH HOSE CLAMPS


AIR & WATER HOSE



RED OR BLACK AVAILABLE

CONSTRUCTION:

Tube: Black EPDM
Reinforcement: Multiple Textile Plies
Cover: EPDM
Pressure Rating: 300 P.S.I. to 1" dia.
 200 P.S.I. @ 1-1/4", 1-1/2" dia.



APPLICATIONS:

Temperature Range: -40°F to +212°F
Fittings: Standard Fittings with Clamps.

Economical and versatile general purpose hose. Excellent for air & water service. EPDM tube and cover resists heat, sunlight, ozone and weathering. GST II hose exceeds RMA class C medium oil resistance requirements. Suitable for applications such as oil mist lubricating air lines, but NOT suitable for the transfer of petroleum products. Closely plied reinforcement of high tensile textile core provides excellent coupling retention and kink resistance. 4:1 pressure safety factor.

HOSE I.D.	HOSE O.D.	MINIMUM BEND RADIUS	APPROX. FULL REEL QTY.	APPROX. WEIGHT (lb/100ft)	SPECIFY PART NO.		PRICE PER FOOT	
					RED	BLACK	CUT LENGTH	*FULL REEL
1/4"	.550"	3.30"	800'	12	7092-4R	7093-4B	\$.68	\$.64
5/16"	.625"	3.50"	750'	13	7092-5R	7093-5B	\$.99	\$.96
3/8"	.688"	4.00"	700'	17	7092-6R	7093-6B	\$.85	\$.80
1/2"	.875"	5.00"	500'	25	7092-8R	7093-8B	\$ 1.07	\$ 1.02
5/8"	1.062"	5.50"	450'	30	7092-10R	7093-10B	\$ 1.60	\$ 1.53
3/4"	1.156"	6.00"	400'	37	7092-12R	7093-12B	\$ 1.30	\$ 1.23
1"	1.438"	8.00"	300'	53	7092-13R	7093-13B	\$ 2.17	\$ 2.11
1-1/4"	1.781"	9.00"	250'	77	7092-14R	7093-14B	\$ 3.84	\$ 3.64
1-1/2"	2.031"	10.00"	230'	86	7092-15R	7093-15B	\$ 4.66	\$ 4.25

SUPER-FLEX® GENERAL SERVICE HOSE

AIR & WATER HOSE



RED OR BLACK AVAILABLE

CONSTRUCTION:

Tube: Black EPDM Rubber
Reinforcement: High Tensile Textile Tire Cord Plies.
Cover: EPDM Rubber-Wrapped Impression.
Pressure Rating: 200 P.S.I.
Standard Lengths: Full Reels 200'

APPLICATIONS:

Temperature Range: -40°F to +212°F
Fittings: Standard Fittings with Clamps.

Highest quality general service air and water hose available. Rigid mandrel construction produces SUPER round, concentric hose for proper flow and coupling ease. Superior adhesion of hose layers provide endurance in tough applications. All this with SUPER flexibility for easier handling. Rated for medium oil resistance for oil mist lubricated air lines; meets RMA class C medium oil resistance, per ASTM D-471. 4:1 pressure safety factor.

HOSE I.D.	HOSE O.D.	MINIMUM BEND RADIUS	APPROX. FULL REEL QTY.	APPROX. WEIGHT (lb/100ft)	SPECIFY PART NO.		PRICE PER FOOT	
					RED	BLACK	CUT LENGTH	*FULL REEL
1-1/4"	1.741"	7.50"	200'	70	7322-14R	7323-14B	\$ 6.74	\$ 6.37
1-1/2"	1.985"	8.50"	200'	80	7322-15R	7323-15B	\$ 7.38	\$ 7.08
2"	2.568"	12.00"	200'	122	7322-16R	7323-16B	\$ 11.63	\$ 11.13

*Note: A full reel may contain up to three pieces.



PLASTIC PROCESS EQUIPMENT, INC.

6385 Montessouri Street, Las Vegas, Nevada 89113
 702-433-6385 • 800-258-8877 • Fax: 702-433-6388

11218 Challenger Avenue, Odessa, Florida 33556
 727-834-8888 • 800-282-6783 • Fax: 727-834-8873

8303 CORPORATE PARK DRIVE, MACEDONIA (Cleveland), OHIO 44056, USA

216-367-7000 • Toll Free: 800-321-0562 • Fax: 216-367-7022 • Order Fax: 800-223-8305

www.ppe.com • e-mail: sales@ppe.com

Toll Free: USA, Canada & Mexico
800-362-0706