




HIGH TEMP INDUSTRIAL HOSE

PARKER X-TREME HOSE

-65°F to 350°F Temperature Range

**HIGH TEMPERATURE SERVICE UP TO 350°F
OIL OR WATER/GLYCOL**



PARKER SILICONE SERIES 6722

Extruded heater hose that meets or exceeds SAEJ20R3 Class A specifications. These hoses are resistant to coolant solutions, cracking, ozone, cold leaks, peeling and aging.

CONSTRUCTION: Red silicone liner, high temperature resistant plies for reinforcement, blue silicone cover.

APPLICATIONS: These hoses are utilized as standard equipment on trucks, cars and busses. It's excellent for high temperature usage in mold temperature control systems.

TEMPERATURE RANGE: -65 to +350°F (-54 to +177°C).

COLOR: Parker 6722 hose is only furnished in BLUE.

SPECIFICATIONS: SAEJ20R3, SAEJ2387

SIZE (IN)	I.D. (IN)	I.D. (MM)	O.D. (IN)	O.D. (MM)	MAX. WORKING PRESSURE (P.S.I.)	BURST (P.S.I.)	WEIGHT (lb/100ft)	BEND RADIUS (IN)	REEL LENGTH	PART NO.	PRICE Cut Length (per ft.)	PRICE Reel Length (per ft.)
1/4	0.250	6	0.526	13	83	250	10.11	0.5	250	6722-0250	\$2.81	\$2.53
3/8	0.375	10	0.690	18	83	250	13.16	0.8	250	6722-0375	\$3.12	\$2.90
1/2	0.500	13	0.815	21	83	250	16.90	1.5	250	6722-0500	\$3.92	\$3.61
5/8	0.625	16	0.940	24	67	250	24.00	1.8	250	6722-0625	\$4.26	\$3.92
3/4	0.750	19	1.065	27	67	200	25.88	2.8	250	6722-0750	\$4.70	\$4.34
7/8	0.875	22	1.213	31	58	175	27.80	4.3	100	6722-0875	\$5.49	\$5.06
1	1.000	25	1.339	34	58	175	33.98	5.0	100	6722-1000	\$6.00	\$5.53



E-Z FORM™ INDUSTRIAL HOSE

AIR & WATER • RATED 75 P.S.I.

★ FOR A TIGHT BEND RADIUS!



GENERAL SERVICE

Specify Parker E-Z Form™ hose #7395 for installations where tight bends exceed the bend radius of other hoses; where the application might otherwise indicate specifying a formed hose.

CONSTRUCTION: EPDM liner, textile plies and helical wire reinforcement, Greek Corrugated EPDM cover.

APPLICATIONS: E-Z Form™ hose is an economical alternative to formed hose - with a lower product cost, reduced inventory and for immediate installation because there is no design, fabrication time or tooling required.

TEMPERATURE RANGE: -40 to +257°F (-40 to +125°C).

COLOR: Parker 7395 hose is only furnished in BLACK with a blue mylar tape stripe with black letters.

SPECIFICATION: SAE J20R1 D-1

HOSE I.D. (IN)	HOSE O.D. (IN)	MAX. WORKING PRESSURE P.S.I.	WEIGHT (LB/FT)	★ MIN. BEND RADIUS (IN)	LENGTH (FT)	PART NO.	PRICE PER 25 FT. LENGTH
1/2"	0.906	75	0.23	1.4	25'	7395-0500	\$204.54 (\$8.18 / ft.)
5/8"	1.024	75	0.27	1.8	25'	7395-0625	\$221.73 (\$8.86 / ft.)
3/4"	1.142	75	0.31	2.0	25'	7395-0750	\$228.76 (\$9.15 / ft.)
1"	1.378	75	0.38	2.0	25'	7395-1000	\$284.93 (\$11.39 / ft.)
1-1/4"	1.693	75	0.50	3.1	25'	7395-1250	\$348.19 (\$13.92 / ft.)
1-1/2"	1.929	75	0.58	3.9	25'	7395-1500	\$415.79 (\$16.63 / ft.)
2"	2.480	75	0.96	5.9	25'	7395-2000	\$512.44 (\$20.49 / ft.)

