



# OLD BULL® MOLD GREASE with PTFE

IDEAL FOR GEARS, CAMS, CABLES, PINS, SLIDES, BEARINGS, CHAINS, LATHES, ETC.

**PPE OLD BULL® PTFE** (polytetrafluoroethylene) **Mold Grease** is a non-silicone, synthetic lubricating grease, specifically formulated for use around the mold. It provides excellent lubrication in both high and low temperature conditions, and also is waterproof and non-melting. It uses a higher concentrated blend of inhibitors that resist rust, corrosion and oxidation. It provides high performance under loads due to its superior load bearing ability. **PPE OLD BULL®** does not contain abrasive clay fillers.

**NO ABRASIVE CLAY FILLERS!**



**NO BULL  
IT'S THE BEST!**

**OLD BULL®  
IS ONLY  
AVAILABLE  
FROM PPE!**

\* Pail has straight sides to accept pump device.

- Softer, thinner formula
- Superior Load Bearing Ability
- Temp. Range: -40 to 500°F
- Color: Beige
- Non-Melting
- Non-Silicone
- Anti-Corrosive
- Waterproof
- Forms an Adherent, but Slippery Film
- Homogenized @ 6,000 psi



**ISO-9002**  
MANUFACTURED IN A  
QUALITY SYSTEM CERTIFIED  
FACILITY.

PART NO.	DESCRIPTION	QUANTITY PRICING		
		1-5	6-11	12+
NBG02	2 oz. Plastic Jar	\$3.65	\$3.50	\$3.35
NBG14	14 oz. Cartridge	11.90	11.40	10.90
NBG16	16 oz. Plastic Jar	13.75	13.30	12.85
*NBG08	8 lb. pail (1 gal.)	89.50	85.00	81.00
*NBG40	40 lb. pail (5 gal.)	435.00	415.00	---

OLD BULL® is a registered trademark of Plastic Process Equipment, Inc.



# OLD BULL® ADVANCED PTFE MOLD GREASE

IDEAL FOR GEARS, CAMS, CABLES, PINS, SLIDES, BEARINGS, CHAINS, LATHES, ETC.

**PPE OLD BULL® ADVANCED FORMULA PTFE Mold Grease** offers a thicker, firmer & less tacky option to the standard Old Bull® Formula, while still providing the same performance and benefits. Its synthetic formula provides excellent lubrication in both high and low temperature conditions, and also is waterproof and non-melting. It uses a higher concentrated blend of inhibitors that resist rust, corrosion and oxidation. It provides high performance under loads due to its superior load bearing ability. **PPE OLD BULL®** does not contain abrasive clay fillers.



**PPE OLD BULL®  
DOES NOT CONTAIN  
ABRASIVE  
CLAY FILLERS!**

**FOOD  
GRADE  
ALSO  
AVAILABLE**

\* Pail has straight sides to accept pump device.

- Thicker, less tacky formula
- Superior Load Bearing Ability
- Temp. Range: -40 to 500°F
- Color: Translucent to off white
- Non-Melting
- Non-Silicone
- Anti-Corrosive
- Waterproof
- Forms an Adherent, but Slippery Film
- Homogenized @ 6,000 psi



**ISO-9002**  
MANUFACTURED IN A  
QUALITY SYSTEM CERTIFIED  
FACILITY.

PART NO.	DESCRIPTION	QUANTITY PRICING		
		1-5	6-11	12+
ABG02	2 oz. Plastic Jar	\$3.80	\$3.65	\$3.50
ABG14	14 oz. Cartridge	12.25	11.75	11.25
ABG16	16 oz. Plastic Jar	14.25	13.80	13.20
*ABG08	8 lb. pail (1 gal.)	91.00	86.50	82.50
*ABG40	40 lb. pail (5 gal.)	440.00	420.00	---

OLD BULL® is a registered trademark of Plastic Process Equipment, Inc.



## PLASTIC PROCESS EQUIPMENT, INC.

**PPE WEST** 6385 Montessouri Street, Las Vegas, Nevada 89113  
702-433-6385 • 800-258-8877 • Fax: 702-433-6388

**PPE SOUTH** 11218 Challenger Avenue, Odessa, Florida 33556  
727-834-8888 • 800-282-6783 • Fax: 727-834-8873

8303 CORPORATE PARK DRIVE, MACEDONIA (Cleveland), OHIO 44056, USA

**PPE** 216-367-7000 • Toll Free: 800-321-0562 • Fax: 216-367-7022 • Order Fax: 800-223-8305

www.ppe.com • e-mail: sales@ppe.com

Toll Free: USA, Canada & Mexico  
**800-362-0706**