



MINI BRASS BALL VALVES

CHROME PLATED

ISO-9002
 MANUFACTURED IN A
 QUALITY SYSTEM CERTIFIED
 FACILITY.

PPE industrial quality, one piece brass bar stock design Mini Brass Ball Valves provide the space savings necessary for small line fluid control applications. Designed for handling compressed air, water, fuels, gases, and other non-corrosive liquids in industrial applications that require compact ball valves. Top-of-the-line features include 235psi MWP Rating, PTFE ball seats for a positive seal in both directions, Viton stem seal, chrome plated brass ball and body for long life and extra corrosion resistance, bottom loaded stem for safety. Corrosion resistant nylon wing handle is compact, easy to use, and clearly shows ball position. Each valve is leak tested to ensure quality. Valve body functions as wrench flats for easy installation.



FEMALE X FEMALE

MALE X FEMALE

FEMALE X FEMALE

Part No.	Thread Size N.P.T.	QUANTITY PRICES	
		1-9	10+
FMV-0018	1/8"	\$5.58	\$5.31
FMV-0014	1/4"	5.26	4.99
FMV-0038	3/8"	5.26	4.99
FMV-0012	1/2"	5.62	5.36

MALE X FEMALE

MMV-0218	1/8"	\$5.37	\$5.15
MMV-0214	1/4"	5.47	5.20
MMV-0238	3/8"	5.48	5.21
MMV-0212	1/2"	6.30	5.97

- Temp Range: 32°F to 176°F
- Threads: Full N.P.T. made to ANSI standards B1.20.1
- Porting: Full on 1/8" & 1/4" sizes
Standard on 3/8" & 1/2" sizes
- Ball Seats: PTFE
- Body: Chrome plated brass hex, one piece forged
- Ball: Chrome plated brass
- Blowout-proof brass stem.
- Stem Seal: Viton
- MWP Rating: 235psi, will handle 300psi @ 75°F
- Handle: Nylon - corrosion resistant
- Each valve is seal tested for safety.
- Double seal system for operation in both directions.
- 1/4 turn handle with mechanical stop.



BRASS MINI-BALL VALVES

WITH STANDARD BARBED INSERT

- Temp Range: 14°F to 212°F
- Threads: 1/8", 1/4" or 3/8" N.P.T.
- 180° Operational 1/4 turn handle with mechanical stop.
- Standard Porting.

- Double seal system for operation in both directions.
- Blowout-proof brass stem.
- 200 WOG rating.
- 125 WSP rating.


- Body: Forged Brass
- Ball: Chrome plated brass
- Ball Seats: PTFE
- Handle: Steel with PVC cover.
- O-Ring: NBR



ISO-9002
 MANUFACTURED IN A
 QUALITY SYSTEM CERTIFIED
 FACILITY.



**GREAT QUALITY!
 GREAT PRICE!**



MALE X HOSE BARB

PART NO.	THREAD SIZE	HOSE I.D.	PRICES	
			1-9	10+
944-138	1/4" NPT	1/4"	\$2.55	\$2.43
944-128	1/4" NPT	3/8"	2.63	2.50

HOSE BARB X HOSE BARB

PART NO.	BARB HOSE I.D.	PRICES	
		1-9	10+
944-142	1/4"	1/4"	\$2.47 \$2.34
944-134	3/8"	3/8"	2.68 2.56

FEMALE X HOSE BARB

PART NO.	THREAD SIZE	HOSE I.D.	PRICES	
			1-9	10+
944-135	1/8" NPT	1/8"	\$3.38	\$3.24
944-121	1/4" NPT	5/16"	2.87	2.73
944-136	1/4" NPT	1/4"	2.39	2.27



PLASTIC PROCESS EQUIPMENT, INC.

6385 Montessouri Street, Las Vegas, Nevada 89113
 702-433-6385 • 800-258-8877 • Fax: 702-433-6388

11218 Challenger Avenue, Odessa, Florida 33556
 727-834-8888 • 800-282-6783 • Fax: 727-834-8873

8303 CORPORATE PARK DRIVE, MACEDONIA (Cleveland), OHIO 44056, USA

216-367-7000 • Toll Free: 800-321-0562 • Fax: 216-367-7022 • Order Fax: 800-223-8305

www.ppe.com • e-mail: sales@ppe.com

Toll Free: USA, Canada & Mexico
800-362-0706