OLD BULL FOOD GRADE PTFE MOLD GREASE

FOR GEARS, CAMS, CABLES, PINS, SLIDES, BEARINGS, CHAINS, ETC., ETC.

PPE OLD BULL® Food Grade PTFE Mold Grease is a non-silicone, synthetic lubricating grease, specifically developed for use around the mold where food approval is needed. It is both NSF H1 rated and Kosher approved. A wide temperature range of -75°F to 500°F allows it to be used in a wide variety of applications. It is non-melting, anticorrosive, non-staining and can withstand high loads due to its superior load bearing ability. PPE OLD BULL® does not contain abrasive clay fillers. - NOTICE -



Food Grade

- NSF H1 Rating
- Kosher Approved
- Non-Staining
- Non-Melting
- Non-Silicone

H1 Lubricants may be used in applications where incidental food contact may potentially occur.

H2 Lubricants can be used in foodprocessing facilities, but only where there is absolutely no possibility of contact with food.

- Temp. Range: -75 to 500°F
- Color: Clear to Translucent
- Forms an Adherent, but Slipperv Film

PART NO.	DESCRIPTION	PRICES		
		1-5	6-11	12+
FMG02	2 oz. Plastic Jar	\$4.10	\$3.95	\$3.80
FMG13	13 oz. Cartridge	\$17.15	\$16.45	\$15.75
FMG15	15 oz. Plastic Jar	\$18.50	\$17.75	\$17.00
* FMG07	7 lb. pail (1 gal.)	\$107.00	\$102.50	\$98.00
* FMG33	33 lb. pail (5 gal.)	\$495.00	\$475.00	

*Pail has straight sides to accept pump device!

OLD BULL® is a registered trademark of Plastic Process Equipment, Inc.

ITE LITHIUM GREASE

FOR GEARS, CAMS, CABLES, PINS, SLIDES, BEARINGS, CHAINS, ETC., ETC.

PPE White Lithium Grease is a white lithium based lubricating grease especially formulated for lubrication of a large variety of equipment over a wide range of operating conditions. It provides excellent lubrication in both high and low temperature conditions, has a dropping point of 360°F and exhibits very good water washout characteristics. It performs well under heavy loads and provides excellent lubrication protection under severe conditions, as it retains its worked stability. PPE White Lithium Grease does not thin out significantly in service and has USDA H-2 rating.



- USDA H-2 Rating
- Temp. Range: -10 to 350°F
- Flash Point: 375°F
- · Color: Off White
- Rust resistant
- Good water washout resistant characteristics
- Also available in aerosol WL-125

PART NO.	DESCRIPTION	PRICES		
		1-5	6-11	12+
WLG08	8 oz. Plastic Tube	\$6.30	\$6.00	\$5.70
WLG14	14 oz. Cartridge	\$9.95	\$9.45	\$8.95
WLG16	16 oz. Plastic Jar	\$10.85	\$10.30	\$9.75
* WLG07	7 lb. pail (1 gal.)	\$79.50	\$75.50	\$71.75
* WLG35	35 lb. pail (5 gal.)	\$307.50	\$290.00	

*Pail has straight sides to accept pump device!



8303 CORPORATE PARK DRIVE **MACEDONIA, OHIO 44056-2300** 216-367-7000 • FAX: 216-367-7022

TOLL FREE: 800-321-0562

PROCESS EQUIPMENT, INC.

6385 MONTESSOURI STREET LAS VEGAS, NEVADA 89113-1186 702-433-6385 • FAX: 702-433-6388 TOLL FREE: 800-258-8877

www.ppe.com

e-mail: sales@ppe.com

Toll Free: USA, Canada & Mexico 800-362-0706

Order Fax: 800-223-8305