



OLD BULL® FOOD GRADE PTFE MOLD GREASE

FOR GEARS, CAMS, CABLES, PINS, SLIDES, BEARINGS, CHAINS, ETC., ETC.

PPE OLD BULL® Food Grade PTFE Mold Grease is a non-silicone, synthetic lubricating grease, specifically developed for use around the mold where food approval is needed. It is both NSF H1 rated and Kosher approved. A wide temperature range of -75°F to 500°F allows it to be used in a wide variety of applications. It is non-melting, anti-corrosive, non-staining and can withstand high loads due to its superior load bearing ability. **PPE OLD BULL®** does not contain abrasive clay fillers.

A true H1 Rated Food Grade Mold Grease



Nonfood Compounds
H1 Registered



- Food Grade
- NSF H1 Rating
- Kosher Approved
- Non-Staining
- Non-Melting
- Non-Silicone
- Temp. Range: -75 to 500°F
- Color: Clear to Translucent
- Forms an Adherent, but Slippery Film

NOTICE

H1 Lubricants may be used in applications where incidental food contact may potentially occur.

H2 Lubricants can be used in food-processing facilities, but only where there is absolutely no possibility of contact with food.

PART NO.	DESCRIPTION	PRICES		
		1-5	6-11	12+
FMG02	2 oz. Plastic Jar	\$4.10	\$3.95	\$3.80
FMG13	13 oz. Cartridge	\$16.75	\$15.95	\$15.15
FMG15	15 oz. Plastic Jar	\$17.90	\$17.15	\$16.40
* FMG07	7 lb. pail (1 gal.)	\$105.00	\$100.50	\$96.00
* FMG33	33 lb. pail (5 gal.)	\$495.00	\$475.00	---

*Pail has straight sides to accept pump device!

OLD BULL® is a registered trademark of Plastic Process Equipment, Inc.



WHITE LITHIUM GREASE

FOR GEARS, CAMS, CABLES, PINS, SLIDES, BEARINGS, CHAINS, ETC., ETC.

PPE White Lithium Grease is a white lithium based lubricating grease especially formulated for lubrication of a large variety of equipment over a wide range of operating conditions. It provides excellent lubrication in both high and low temperature conditions, has a dropping point of 360°F and exhibits very good water washout characteristics. It performs well under heavy loads and provides excellent lubrication protection under severe conditions, as it retains its worked stability. **PPE White Lithium Grease** does not thin out significantly in service and has USDA H-2 rating.

ISO-9002
MANUFACTURED IN A
QUALITY SYSTEM CERTIFIED
FACILITY.



- USDA H-2 Rating
- Temp. Range: -10 to 350°F
- Flash Point: 375°F
- Color: Off White
- Rust resistant
- Good water washout resistant characteristics
- Also available in aerosol WL-125

BETTER PRICE BREAKS!



PART NO.	DESCRIPTION	PRICES		
		1-5	6-11	12+
WLG08	8 oz. Plastic Tube	\$5.45	\$5.20	\$4.95
WLG14	14 oz. Cartridge	\$8.65	\$8.25	\$7.85
WLG16	16 oz. Plastic Jar	\$9.10	\$8.70	\$8.30
* WLG07	7 lb. pail (1 gal.)	\$71.50	\$68.25	\$65.00
* WLG35	35 lb. pail (5 gal.)	\$249.00	\$236.00	---

*Pail has straight sides to accept pump device!



PLASTIC PROCESS EQUIPMENT, INC.

EAST 8303 CORPORATE PARK DRIVE
MACEDONIA, OHIO 44056
216-367-7000 • FAX: 216-367-7022
TOLL FREE: 800-321-0562

WEST 6385 MONTESSOURI STREET
LAS VEGAS, NEVADA 89113
702-433-6385 • FAX: 702-433-6388
TOLL FREE: 800-258-8877

www.ppe.com
e-mail: sales@ppe.com

Toll Free: USA, Canada & Mexico
800-362-0706

Order Fax: 800-223-8305