CERAMIC HEATER BANDS

3 TYPES AVAILABLE

SAVE ENERGY - USE LESS ELECTRICITY

3 TYPES AVAILABLE

1.) MAX: 1/2" Insulation x 15/16" thick O.A.
2.) Standard: 1/4" Insulation x 5/8" thick O.A.
3.) UltraThin: 3/16" Insulation x 3/8" thick O.A.



INSULATION MAX® TYPE SHOWN A FULL 1/2" TOTAL INSULATION 15/16" THICK



- SPECIFICATIONS -

- Expandable, will open fully to fit around barrel O.D.
- 5/8" high lock-up flanges standard or barrel nut clamp optional N/C.
- 1/4-20 post terminals located 180° from gap.
- All stainless steel sheath.

TO ORDER SPECIFY

1. Ceramic design.
2. Inside diameter x width.
3. Voltage and wattage.
4. Lock-up option, flange or barrel nut clamp.
5. Post terminals or other type.
6. Terminal box if required.
7. Thermocouple hole and location.

INSULATION MAX® EMPLOYS AN ADDITIONAL 1/4" OF HIGH DENSITY CERAMIC-FIBER INSULATION ENCASED IN A SEPARATE FLEXIBLE STAINLESS STEEL SHELL.

THE INSULATION IS NOT COMPRESSED WHICH PROVIDES MAXIMUM R VALUE.

Genuine O.E.M. Replacements

Also available in Standard Construction and Ultra Thin.

INSULATION MAX® is a registered trademark of Plastic Process Equipment, Inc.

SAVE ENERGY - USE LESS ELECTRICITY

PLASTIC PROCESS EQUIPMENT, INC.
www.ppe.com • e-mail: sales@ppe.com
PPE WEST 6385 Montessouri Street, Las Vegas, Nevada 89113
702-433-6385 • 800-258-8877 • Fax: 702-433-6388
PPE SOUTH 11218 Challenger Avenue, Odessa, Florida 33556
727-834-8888 • 800-282-6783 • Fax: 727-834-8873
PPE 8303 CORPORATE PARK DRIVE, MACEDONIA (Cleveland), OHIO 44056, USA
216-367-7000 • Toll Free: 800-321-0562 • Fax: 216-367-7022 • Order Fax: 800-223-8305
Toll Free: USA, Canada & Mexico 800-362-0706