



DIGITAL MULTIMETERS

**NEW
MORE FEATURES!**



**HUGE
1.4 Inch Digits!**

MODEL 1101-B

Compact
Digital Multimeter
with Backlight &
Temperature Test

CAT II 600V

Test Leads Included



Features

- Compact DMM
- 3 -1/2 Digit, High Contrast LCD with 0.50" Digits
- Rugged Double-Insulated Case Design
- 5 DC Voltage Ranges
- 2 AC Voltage Ranges, 200V & 600V
- 4 DC Current Ranges
- 5 Resistance Ranges
- Diode Test
- Temperature Test (probe included)
- Continuity Beeper
- Transistor hFE (Gain) Test
- Low Battery Indication
- Built-in Stand
- Overload Protection
- Auto Power Off
- Data Hold
- CAT II 600V Certified
- 3 Year Limited Warranty

1101-B General Specifications

Display: 3-1/2 Digital LCD, (0.5" digits) with maximum reading of 1999.

Polarity: Automatic (-) negative polarity indication.

Over Range Indication: LCD will display "1" or "-1".

Low Battery Indication: Replace battery when battery symbol is displayed.

Operating Temperature & Humidity: 0°C to 40°C, 80%RH

Power Supply: One standard 9V battery PPE #EN22 (Included)

Battery Life: Approximately 150 hours.

Weight: Approximately 6 oz. with battery (170g).

Dimensions: 5.5"(L) x 2.7"(W) x 1.2"(H) [140 (L) x 69 (W) x 31 (H) mm].

Accessories Included: Instruction Manual, Test Leads, Thermocouple, Battery, Spare Fuse, Rubber Boot. (Carrying Case not included.)

Model 1101-B and Accessories

Part No.	Description	Price
1101-B	Compact Digital MultiMeter	\$42.60
79-760	Test Leads w/ screw-on alligator clips (90°)	10.50

MODEL 9007-A

Professional
Digital Multimeter
with Backlight
& Capacitance
30 Measurement
Ranges

CAT III 600V

Test Leads Included



Features

- Hand Sized DMM
- 3 -1/2 Digit, High Contrast LCD with 1.4" Digits
- Rugged Case Design with protective shock absorbing overmolded shell
- 5 DC Voltage Ranges
- 5 AC Voltage Ranges
- 4 DC Current Ranges
- 3 AC Current Ranges
- 7 Resistance Ranges
- 600 Volts AC & DC
- 5 Capacitance Ranges
- Diode Test
- Continuity Beeper
- Capacitance Test
- Low Battery Indication
- Overrange Indication
- Overload Protected
- Auto Power Off
- Built-in Stand
- 3 Year Limited Warranty
- CAT III 600V Certified

9007-A General Specifications

Display: 3-1/2 Digital LCD, (1.4" digits) with maximum reading of 1999.

Polarity: Automatic (-) negative polarity indication.

Over Range Indication: First digit displays "1", remaining digits are blank.

Low Battery Indication: Replace battery when battery symbol is displayed.

Measurement Rate: 2 times per second.

Operating Temperature & Humidity: 0°C to 50°C, below 70%RH.

Storage Temperature & Humidity: -20°C to 60°C, below 80%RH.

Power Supply: One standard 9V battery PPE #EN22 (Included)

Battery Life: Approximately 200 hours.

Weight: Approximately 14 oz.

Dimensions: 7.0"(L) x 3.2"(W) x 2.2"(H) [178 (L) x 82 (W) x 56 (H) mm].

Accessories Included: Instruction Manual, Test Leads & Battery. (Carrying Case not included.)

Model 9007-A and Accessories

Part No.	Description	Price
9007-A	Digital MultiMeter	\$68.30
79-760	Test Leads w/ screw-on alligator clips (90°)	10.50



PLASTIC PROCESS EQUIPMENT, INC.

6385 Montessouri Street, Las Vegas, Nevada 89113
PPE WEST 702-433-6385 • 800-258-8877 • Fax: 702-433-6388

11218 Challenger Avenue, Odessa, Florida 33556
PPE SOUTH 727-834-8888 • 800-282-6783 • Fax: 727-834-8873

8303 CORPORATE PARK DRIVE, MACEDONIA (Cleveland), OHIO 44056, USA

216-367-7000 • Toll Free: 800-321-0562 • Fax: 216-367-7022 • Order Fax: 800-223-8305

www.ppe.com • e-mail: sales@ppe.com

Toll Free: USA, Canada & Mexico
800-362-0706