SAFETY DATA SHEET

OSHA HCS (29 CFR 1910.1200)

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

Product identifier

Chemical Name Mixture CAS No. Mixture

Trade Name PPE PAINTABLE ECONO MOLD RELEASE EP-161

Product Code 10-501861

Relevant identified uses of the substance or mixture and uses advised against

Identified Use(s) Mold Release Uses Advised Against None

Company Identification Plastic Process Equipment, Inc

8303 Corporate Park Drive Macedonia, OH 44056

 Telephone
 (800) 362-0706

 Fax
 (216) 367-7022

 E-Mail (competent person)
 Sales@ppe.com

Emergency telephone number

Emergency Phone No. (216) 566-2917 Transportation Emergency: (800) 424-9300

SECTION 2: HAZARDS IDENTIFICATION

Classification of the substance or mixture

OSHA HCS (29 CFR 1910.1200) Flam. Aerosol 1; Compressed dissolved gas; Skin Irrit. 2; Eye Irrit. 2;

STOT SE 3; Asp. Tox. 1

Label elements

Hazard Symbol



Signal word(s) DANGER

Hazard Statement(s) Extremely flammable aerosol.

Contains gas under pressure; may explode if heated. Repeated exposure may cause skin dryness or cracking.

May cause drowsiness or dizziness.

Precautionary Statement(s) Keep away from heat/sparks/open flames/hot surfaces. – No smoking.

Do not spray on an open flame or other ignition source.

Avoid breathing spray.

Protect from sunlight and do not expose to temperatures exceeding 50

°C/122 °F.

Wash hands and exposed skin after use.

Keep out of reach of children.

Other hazards None

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous Ingredient(s)	% wt. *	CAS No.	Hazard classification
Heptane, branched, cyclic and linear	70-90	426260-76-6	Flam. Liq. 2; H225 Asp. Tox. 1; H304 Skin Irrit. 2; H315 STOT SE 3; H336
Propane	20-35	74-98-6	Flam. Gas 1; H220 Liquefied gas; H280
Siloxanes and Silicones, lauryl Me, Me 2-phenylpropyl	0.5-2	68037-76-3	Not classified as dangerous for supply/use.

Additional Information - None

SECTION 4: FIRST AID MEASURES



Description of first aid measures

Inhalation Move person to fresh air. If breathing is labored, administer oxygen. If

symptoms develop, obtain medical attention.

Skin Contact Wash affected skin with soap and water. If symptoms develop, obtain

medical attention.

Eye Contact IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing. If symptoms

occur obtain medical attention.

Ingestion Do not give anything by mouth to an unconscious person. Seek medical

treatment.

Most important symptoms and effects, both acute and

delayed

May cause damage to organs: (Optic nerve, Central nervous system)

Indication of any immediate medical attention and

special treatment needed

IF SWALLOWED: Immediately call a POISON CENTER or

doctor/physician.

SECTION 5: FIRE-FIGHTING MEASURES

Extinguishing Media

-Suitable Extinguishing Media

-Unsuitable Extinguishing Media

Extinguish with carbon dioxide, dry chemical, foam or water spray. Do not use water jet.

Special hazards arising from the substance or

mixture

Highly flammable vapor (flash point below 23°C).

Advice for fire-fighters

A self contained breathing apparatus and suitable protective clothing should be worn in fire conditions. Keep containers cool by spraying

with water if exposed to fire.

^{*} The exact percentage withheld as a trade secret in accordance with 29 CFR 1910.1200.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and Keep away from heat/sparks/open flames/hot surfaces. – No smoking.

emergency procedures Take precautionary measures against static discharges. Avoid contact

with skin and eyes. Avoid breathing vapors.

Environmental precautions Prevent liquid entering sewers, basements and work pits.

Methods and material for containment and cleaning up Cover spills with inert absorbent material. Transfer to a container for

disposal or recovery.

Reference to other sections None
Additional Information None

SECTION 7: HANDLING AND STORAGE

Precautions for safe handling Keep away from heat/sparks/open flames/hot surfaces. – No

smoking. Avoid contact with skin and eyes. Use product in a well-

ventilated area only.

Conditions for safe storage, including any incompatibilities

-Storage temperature Keep in a cool, well ventilated place. Store at temperatures not

exceeding 50 °C / 122 °F.

-Incompatible materials This product should be stored away from sources of strong heat or

oxidizing chemicals.

Specific end use(s) Belt dressing

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Occupational Exposure Limits

		(8hr TWA)		(STEL)		
SUBSTANCE.	CAS No.	PEL (OSHA)	TLV (ACGIH)	PEL (OSHA)	TLV (ACGIH)	Note:
Heptane, branched, cylic and linear	426260-76-6	500 ppm*	1500 mg/m ³			*n-heptane
n-Butane	106-97-8		250 ppm			
Propane	74-98-6	1000 ppm	Aspyx.#			#

[^]NIC = Notice of Intended Changes (ACGIH®);

Recommended monitoring method

NIOSH 1300 (Ketones I); NIOSH 2000 (Methanol); NIOSH 1500

(hydrocarbons, B.P. 36 - 126 °C)

Exposure controls

Appropriate engineering controls Provide adequate ventilation to ensure that the occupational exposure

limit is not exceeded.

Personal protection equipment

Eye/face protection Wear protective eyewear (goggles, face shield, or safety glasses).

Skin protection (Hand protection/ Other)

Wear suitable gloves if prolonged skin contact is likely (Nitrile rubber)



Respiratory protection



Normally no personal respiratory protection is necessary. In case of insufficient ventilation, wear suitable respiratory equipment.

Thermal hazards

Not normally required. Use gloves with insulation for thermal $% \left(1\right) =\left(1\right) \left(1\right$

protection, when needed.

Environmental Exposure Controls None known

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Appearance Liquid
Color. Colorless
Odor Acetone-like
Odor Threshold (ppm) Not available
pH (Value) Not available
Melting Point (°C) / Freezing Point (°C) Not available
Boiling point/boiling range (°C): 56 (Acetone)

Boiling point/boiling range (°C):

Flash Point (°C)

Evaporation Rate

Flammability (solid, gas)

Solid (Acetone)

-17 (Acetone)

Not available

Not available

Explosive Limit Ranges 2.1% - 9.5% v/v (Propane) Vapor pressure (Pascal) ca. 95 x 10^4 (Propane) Vapor Density (Air=1) ca. 1.56 @ 0°C (Propane)

Density (g/ml)

Solubility (Water)

Solubility (Other)

Partition Coefficient (n-Octanol/water)

Auto Ignition Point (°C)

Decomposition Temperature (°C)

Not available

Not available

465 (Acetone)

Not available

Kinematic Viscosity <20

Explosive properties Not explosive.
Oxidizing properties Not oxidizing.

Other information Not available

SECTION 10: STABILITY AND REACTIVITY

Reactivity Stable under normal conditions.

Chemical stability Stable.

Possibility of hazardous reactions None anticipated.

Conditions to avoidAvoid contact with heat and ignition sources.

Incompatible materials Strong oxidizing agents

Hazardous decomposition product(s) Carbon monoxide, Carbon dioxide, Acrid smoke

SECTION 11: TOXICOLOGICAL INFORMATION

Exposure routes: Inhalation, Skin Contact, Eye Contact

Information on toxicological effects

Propane (CAS# 74-98-6):

Acute toxicity Inhalation: LC50 = 1237 mg/L (2-hr, mouse, gas)

Irritation/Corrosivity No evidence of irritant effects from normal handling and use.

Sensitisation It is not a skin sensitiser.

Repeated dose toxicity

NOAEC: ≥19678 mg/m3 (28-day, rat, Systemic effects)

LOAEC: 21641 mg/m3 (28-day, rat, effects: Body weight)

Carcinogenicity No data. It is unlikely to present a carcinogenic hazard to man.

Mutagenicity There is no evidence of mutagenic potential.

Reproductive toxicity

None anticipated

Exposure routes: Inhalation, Skin Contact, Eye Contact

Heptane, branched, cylic and linear (CAS# 426260-76-6) - By analogy with similar materials:

Acute toxicity Oral: LD50 >5 g/kg-bw

Dermal: LD50 >2 g/kg-bw

Inhalation: LC50 = 65 - 103 mg/L (Vapor), 4-hr. rat

May cause drowsiness or dizziness.

May be fatal if swallowed and enters airways.

Irritation/Corrosivity Causes skin irritation. Repeated exposure may cause skin dryness

or cracking. May cause eye irritation.

Sensitization It is not a skin sensitizer.

Repeated dose toxicity NOAEC: 12350 mg/m3 (2 yr, inhal., rat, Systemic effects)

LOAEC: 1650 mg/m3 (2 hr, inhal., rat, CNS effects)

May cause drowsiness or dizziness.

Carcinogenicity No data. It is unlikely to present a carcinogenic hazard to man.

NTP	IARC	ACGIH	OSHA	NIOSH
No.	No.	No.	No.	No.

Mutagenicity There is no evidence of mutagenic potential.

Reproductive toxicity Not available

SECTION 12: ECOLOGICAL INFORMATION

Heptane, branched, cylic and linear (CAS# 426260-76-6) - By analogy with similar materials:

Short term LL50 (96 hour): >13.4 mg/L (Oncorhynchus mykiss)

EL50 (48 hour): 3 mg/l (Daphnia magna, mobility)

EC50 (96 hour): 13 mg/l (Pseudokirchnerella subcapitata)

Long Term NOELR (28 days) 1.5 mg/l (Fish) QSAR

LOEC (21 days): 0.32 mg/l (Daphnia magna)

NOEL (96 hour) 6.3 mg/l (Algae)

Persistence and degradability Readily biodegradable.

Bioaccumulative potential The product has no potential for bioaccumulation.

Mobility in soil Not available.

Results of PBT and vPvB assessmentNot classified as PBT or vPvB.

Other adverse effects None known.

SECTION 13: DISPOSAL CONSIDERATIONS

Waste treatment methods Disposal should be in accordance with local, state or national

legislation. Consult an accredited waste disposal contractor or the

local authority for advice.

SECTION 14: TRANSPORT INFORMATION

Sea transport Air transport U.S. DOT (IMDG) (ICAO/IATA) **UN** number 1950 1950 1950 **Proper Shipping Name** Aerosols, flammable Aerosols, flammable Aerosols, flammable Transport hazard class(es) 2.1 2.1 2.1 **Packing group** Not applicable Not applicable Not applicable **Environmental hazards** None assigned None assigned None assigned Special precautions for user None assigned None assigned None assigned

Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code: Not applicable

SECTION 15: REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture:

TSCA (Toxic Substance Control Act) - Inventory Status: All components listed or polymer exempt.

Designated Hazardous Substances and Reportable Quantities (40 CFR 302.4):

Chemical Name	CAS No.	Typical %wt.	RQ (Pounds)
None			

SARA 311/312 - Hazard Categories: See SECTION 2: HAZARDS IDENTIFICATION

SARA 313 - Toxic Chemicals (40 CFR 372):

Chemical Name	CAS No.	Typical %wt.
none		

SARA 302 - Extremely Hazardous Substances(40 CFR 355):

Chemical Name	CAS No.	Typical %wt.	TPQ (pounds)
None			

California Proposition 65 List:

Chemical Name	CAS No.	Type of Toxicity
None		

SECTION 16: OTHER INFORMATION

The following sections contain revisions or new statements: 1-16.

Date of preparation: August 10, 2020

Hazard Statement(s) and Risk Phrases Listed in: SECTION 2:/ SECTION 3:

Hazard Statement(s)

- -H220: Extremely flammable gas.
- H225: Highly flammable liquid and vapor.
- H304: May be fatal if swallowed and enters airways.
- H315: Causes skin irritation.
- H336: May cause drowsiness or dizziness.

Training advice: None.

Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.