



MATERIAL SAFETY DATA SHEET

(Complies with OSHA Communication Standard 29 CFR 1910.1200 Dept. of Labor)

Form approved OMB No. 1218-0072

OSHA 174 - September 1985

HMIS RATING	
HEALTH	
FLAMMABILITY	
REACTIVITY	
NFPA RATING	
HEALTH	
FLAMMABILITY	
REACTIVITY	

IDENTITY:

HFT-36 / HFT-37

Marketer's Name Must Appear Below	DOT Shipping- Consumer commodity ORM-D
Manufacturer's Name Plastic Process Equipment, Inc.	Emergency Telephone Number 1-800-535-5053
Address 8303 Corporate Park Drive	Telephone Number for Information (216) 367-7000
Macedonia, Ohio 44056	Date Prepared 10/18/07 CHECKED

Section 2- Hazardous Ingredients/Identity Information

Hazardous Components (Specific Chemical Identity, Common Name(s))	OSHA PEL	ACGIH TLV	IDLH	% (optional)
NA				

All chemical compounds marked with an asterisk () are toxic chemicals subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372. You must notify each person to whom this mixture or trade name product is sold. This statement must remain a part of this Material Safety Data Sheet.

Section 3- Physical/Chemical Characteristics

Boiling Point	Range	NA	Specific Gravity (H ₂ O=1)	NA
Vapor Pressure @ 70°F		NA	Melting Point	NA
Vapor Density (Air=1)	Heavier than air	NA	Evaporation Rate	NA
			(Butyl Acetate = 1)	
Solubility in Water	< 0.1%		Appearance and Odor	LIGHT GOLDEN COLOR, CLOTH APPEARANCE WITH NO ODOR

Section 4- Fire and Explosion Hazard Data

Flash Point (Method Used)	NA	Flammable Limits	ND	LEL	ND	UEL	ND
Extinguishing Media	NA						
Special Fire Fighting Procedures	NA						
Unusual Fire and Explosion Hazards	NA						

