

DOW CORNING(R) 200 FLUID, 350 CST.

Version Revision Date: SDS Number: Date of last issue: 04/21/2016
2.1 10/31/2016 1307340-00007 Date of first issue: 02/12/2015

SECTION 1. IDENTIFICATION

Product name : DOW CORNING(R) 200 FLUID, 350 CST.
Product code : 000000000001013211

Manufacturer or supplier's details

Company name of supplier : Dow Corning Corporation
Address : South Saginaw Road
 : Midland Michigan 48686
Telephone : (989) 496-6000
Emergency telephone : 24 Hour Emergency Telephone : (989) 496-5900
 : CHEMTREC : (800) 424-9300

Recommended use of the chemical and restrictions on use

Recommended use : Intermediate
 : Solvent
 : Process regulators, other than polymerization or vulcanization
 : processes
 : Cosmetics

SECTION 2. HAZARDS IDENTIFICATION**GHS classification in accordance with 29 CFR 1910.1200**

Not a hazardous substance or mixture.

GHS label elements

Not a hazardous substance or mixture.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Substance
Substance name : Dimethyl siloxane, trimethylsiloxy-terminated
CAS-No. : 63148-62-9
Chemical nature : Silicone

Hazardous ingredients

No hazardous ingredients

SECTION 4. FIRST AID MEASURES

DOW CORNING(R) 200 FLUID, 350 CST.

Version	Revision Date:	SDS Number:	Date of last issue: 04/21/2016
2.1	10/31/2016	1307340-00007	Date of first issue: 02/12/2015

- If inhaled : If inhaled, remove to fresh air.
Get medical attention if symptoms occur.
- In case of skin contact : Wash with water and soap as a precaution.
Get medical attention if symptoms occur.
- In case of eye contact : Flush eyes with water as a precaution.
Get medical attention if irritation develops and persists.
- If swallowed : If swallowed, DO NOT induce vomiting.
Get medical attention if symptoms occur.
Rinse mouth thoroughly with water.
- Most important symptoms and effects, both acute and delayed : None known.
- Protection of first-aiders : No special precautions are necessary for first aid responders.
- Notes to physician : Treat symptomatically and supportively.

SECTION 5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media : Water spray
Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical
- Unsuitable extinguishing media : None known.
- Specific hazards during fire fighting : Exposure to combustion products may be a hazard to health.
- Hazardous combustion products : Carbon oxides
Silicon oxides
Formaldehyde
- Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Use water spray to cool unopened containers.
Remove undamaged containers from fire area if it is safe to do so.
Evacuate area.
- Special protective equipment for fire-fighters : Wear self-contained breathing apparatus for firefighting if necessary.
Use personal protective equipment.

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency measures : Follow safe handling advice and personal protective equipment recommendations.

DOW CORNING(R) 200 FLUID, 350 CST.

Version Revision Date: SDS Number: Date of last issue: 04/21/2016
2.1 10/31/2016 1307340-00007 Date of first issue: 02/12/2015

gency procedures

Environmental precautions : Discharge into the environment must be avoided.
Prevent further leakage or spillage if safe to do so.
Prevent spreading over a wide area (e.g. by containment or oil barriers).
Retain and dispose of contaminated wash water.
Local authorities should be advised if significant spillages cannot be contained.

Methods and materials for containment and cleaning up : Soak up with inert absorbent material.
For large spills, provide diking or other appropriate containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate container.
Clean up remaining materials from spill with suitable absorbent.
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

SECTION 7. HANDLING AND STORAGE

Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.

Local/Total ventilation : Use only with adequate ventilation.

Advice on safe handling : Handle in accordance with good industrial hygiene and safety practice.
Take care to prevent spills, waste and minimize release to the environment.

Conditions for safe storage : Keep in properly labeled containers.
Store in accordance with the particular national regulations.

Materials to avoid : Do not store with the following product types:
Strong oxidizing agents

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**Ingredients with workplace control parameters**

Contains no substances with occupational exposure limit values.

Engineering measures : Processing may form hazardous compounds (see section 10).
Ensure adequate ventilation, especially in confined areas.
Minimize workplace exposure concentrations.

DOW CORNING(R) 200 FLUID, 350 CST.

Version 2.1 Revision Date: 10/31/2016 SDS Number: 1307340-00007 Date of last issue: 04/21/2016
Date of first issue: 02/12/2015

Personal protective equipment

- Respiratory protection : No personal respiratory protective equipment normally required.
- Hand protection
- Remarks : Wash hands before breaks and at the end of workday.
- Eye protection : Wear the following personal protective equipment:
Safety glasses
- Skin and body protection : Skin should be washed after contact.
- Hygiene measures : Ensure that eye flushing systems and safety showers are located close to the working place.
When using do not eat, drink or smoke.
Wash contaminated clothing before re-use.
These precautions are for room temperature handling. Use at elevated temperature or aerosol/spray applications may require added precautions.
For further information regarding the use of silicones / organic oils in consumer aerosol applications, please refer to the guidance document regarding the use of these type of materials in consumer aerosol applications that has been developed by the silicone industry (www.SEHSC.com) or contact the Dow Corning customer service group.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

- Appearance : liquid
- Color : colorless
- Odor : characteristic
- Odor Threshold : No data available
- pH : No data available
- Melting point/freezing point : No data available
- Initial boiling point and boiling range : > 35 °C
- Flash point : > 120 °C
Method: closed cup
- Evaporation rate : No data available
- Flammability (solid, gas) : Not applicable
- Self-ignition : The substance or mixture is not classified as pyrophoric. The substance or mixture is not classified as self heating.

SAFETY DATA SHEET

DOW CORNING

DOW CORNING(R) 200 FLUID, 350 CST.

Version 2.1 Revision Date: 10/31/2016 SDS Number: 1307340-00007 Date of last issue: 04/21/2016
Date of first issue: 02/12/2015

Upper explosion limit : No data available
Lower explosion limit : No data available
Vapor pressure : No data available
Relative vapor density : No data available
Relative density : 0.97
Solubility(ies)
 Water solubility : No data available
Partition coefficient: n-octanol/water : No data available
Autoignition temperature : No data available
Decomposition temperature : No data available
Viscosity
 Viscosity, kinematic : 350 cSt

Explosive properties : Not explosive
Oxidizing properties : The substance or mixture is not classified as oxidizing.
Molecular weight : No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity : Not classified as a reactivity hazard.
Chemical stability : Stable under normal conditions.
Possibility of hazardous reactions : Can react with strong oxidizing agents.
When heated to temperatures above 150 °C (300 °F) in the presence of air, trace quantities of formaldehyde may be released.
Adequate ventilation is required.
See OSHA formaldehyde standard, 29 CFR 1910.1048
Hazardous decomposition products will be formed at elevated temperatures.
Conditions to avoid : None known.
Incompatible materials : Oxidizing agents

Hazardous decomposition products

Thermal decomposition : Formaldehyde

DOW CORNING(R) 200 FLUID, 350 CST.

Version Revision Date: SDS Number: Date of last issue: 04/21/2016
2.1 10/31/2016 1307340-00007 Date of first issue: 02/12/2015

SECTION 11. TOXICOLOGICAL INFORMATION**Information on likely routes of exposure**

Inhalation
Skin contact
Ingestion
Eye contact

Acute toxicity

Not classified based on available information.

Product:

Acute oral toxicity : LD50 (Rat): > 15,400 mg/kg
Assessment: The substance or mixture has no acute oral toxicity
Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg
Assessment: The substance or mixture has no acute dermal toxicity
Remarks: Based on data from similar materials

Skin corrosion/irritation

Not classified based on available information.

Product:

Species: Rabbit
Result: No skin irritation
Remarks: Based on data from similar materials

Serious eye damage/eye irritation

Not classified based on available information.

Product:

Species: Rabbit
Result: No eye irritation
Remarks: Based on data from similar materials

Respiratory or skin sensitization**Skin sensitization**

Not classified based on available information.

Respiratory sensitization

Not classified based on available information.

Product:

Assessment: Does not cause skin sensitization.

Test Type: Maximization Test
Species: Guinea pig
Remarks: On basis of test data.

DOW CORNING(R) 200 FLUID, 350 CST.

Version	Revision Date:	SDS Number:	Date of last issue: 04/21/2016
2.1	10/31/2016	1307340-00007	Date of first issue: 02/12/2015

Germ cell mutagenicity

Not classified based on available information.

Product:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative
Remarks: Based on data from similar materials

Carcinogenicity

Not classified based on available information.

Product:

Species: Rat
Application Route: Ingestion
Result: negative
Remarks: Based on data from similar materials

Carcinogenicity - Assessment : Animal testing did not show any carcinogenic effects.

IARC

No ingredient of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

OSHA

No ingredient of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

NTP

No ingredient of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

Reproductive toxicity

Not classified based on available information.

Product:

Effects on fertility : Species: Rabbit, male
Application Route: Ingestion
Symptoms: No effects on fertility.
Remarks: Based on data from similar materials

Effects on fetal development : Test Type: Prenatal development toxicity study (teratogenicity)
Species: Rabbit, female
Application Route: Skin contact
Symptoms: No effects on fetal development.
Remarks: On basis of test data.

Reproductive toxicity - Assessment : No evidence of adverse effects on sexual function and fertility, or on development, based on animal experiments.

STOT-single exposure

Not classified based on available information.

DOW CORNING(R) 200 FLUID, 350 CST.

Version Revision Date: SDS Number: Date of last issue: 04/21/2016
2.1 10/31/2016 1307340-00007 Date of first issue: 02/12/2015

STOT-repeated exposure

Not classified based on available information.

Product:

Routes of exposure: Ingestion

Assessment: No significant health effects observed in animals at concentrations of 100 mg/kg bw or less.

Routes of exposure: Skin contact

Assessment: No significant health effects observed in animals at concentrations of 200 mg/kg bw or less.

Repeated dose toxicity

Product:

Species: Rat

Application Route: Ingestion

Remarks: On basis of test data.

Species: Rabbit

Application Route: Skin contact

Remarks: On basis of test data.

Aspiration toxicity

Not classified based on available information.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 200 mg/l
Exposure time: 48 h

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Resource Conservation and Recovery Act (RCRA) : This product has been evaluated for RCRA characteristics and does not meet the criteria of hazardous waste if discarded in its purchased form.

DOW CORNING(R) 200 FLUID, 350 CST.

Version	Revision Date:	SDS Number:	Date of last issue: 04/21/2016
2.1	10/31/2016	1307340-00007	Date of first issue: 02/12/2015

Waste from residues : Dispose of in accordance with local regulations.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.
If not otherwise specified: Dispose of as unused product.

SECTION 14. TRANSPORT INFORMATION**International Regulations****UNRTDG**

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation**49 CFR**

Not regulated as a dangerous good

SECTION 15. REGULATORY INFORMATION**EPCRA - Emergency Planning and Community Right-to-Know****CERCLA Reportable Quantity**

This material does not contain any components with a CERCLA RQ.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : No SARA Hazards**SARA 313** : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.**US State Regulations****Pennsylvania Right To Know**

Dimethyl siloxane, trimethylsiloxy-terminated

63148-62-9

California Prop. 65

This product does not contain any chemicals known to the State of California to cause cancer, birth, or any other reproductive defects.

The ingredients of this product are reported in the following inventories:

SAFETY DATA SHEET

DOW CORNING

DOW CORNING(R) 200 FLUID, 350 CST.


Version 2.1 Revision Date: 10/31/2016 SDS Number: 1307340-00007 Date of last issue: 04/21/2016
Date of first issue: 02/12/2015

NZIoC	:	All ingredients listed or exempt.
REACH	:	All ingredients (pre-)registered or exempt.
TSCA	:	All chemical substances in this product are either listed on the TSCA Inventory or are in compliance with a TSCA Inventory exemption.
AICS	:	All ingredients listed or exempt.
IECSC	:	All ingredients listed or exempt.
ENCS/ISHL	:	All components are listed on ENCS/ISHL or exempted from inventory listing.
KECI	:	All ingredients listed, exempt or notified.
PICCS	:	All ingredients listed or exempt.
DSL	:	All chemical substances in this product comply with the CEPA 1999 and NSNR and are on or exempt from listing on the Canadian Domestic Substances List (DSL).
TCSI	:	All ingredients listed or exempt.

SECTION 16. OTHER INFORMATION

Further information

NFPA:



HMIS® IV:

HEALTH	/	0
FLAMMABILITY		1
PHYSICAL HAZARD		0

HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Full text of other abbreviations

AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Haz-

DOW CORNING(R) 200 FLUID, 350 CST.

Version	Revision Date:	SDS Number:	Date of last issue: 04/21/2016
2.1	10/31/2016	1307340-00007	Date of first issue: 02/12/2015

ardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Sources of key data used to compile the Material Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Revision Date : 10/31/2016

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

US / Z8