# SAFETY DATA SHEET.

Issuing date 05-Dec-2017

Revision Date 02-Jan-2018

Version 1.04

# 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

#### Product identifier Product name

S-206 SUPER SILICONE SPRAY

# Recommended use of the chemical and restrictions on use

Product code
--------------

F02607

Product Type Synonyms Extremely Flammable Aerosol None

Supplier's details

Recommended Use Uses advised against Silicone Mold Spray Release. No information available

#### Manufacturer:

Plastic Process Equipment,Inc. 8303 Corporate Park Dr. Macedonia, Ohio 44056 Phone: 800-321-0562

Emergency telephone number

Chemical Emergency Phone Number Company Emergency Phone Number (1-800-262-8200 ID 1195 (UNITED STATES)

# 2. HAZARDS IDENTIFICATION

## **Classification**

Skin corrosion/irritation	Category 2
Reproductive Toxicity	Category 2
Specific target organ toxicity (single exposure)	Category 3
Specific target organ toxicity (repeated exposure)	Category 2
Aspiration toxicity	Category 1
Flammable aerosols	Category 1
Gases under pressure	Compressed Gas

#### <u>GHS Label elements, including</u> precautionary statements

### DANGER

#### Emergency Overview

# Hazard Statements

Causes skin irritation

Suspected of damaging fertility or the unborn child

May cause respiratory irritation. May cause drowsiness or dizziness.

May cause damage to organs (Eyes, Skin, Respiratory System, Central Nervous System, and Peripheral Nervous System) through prolonged or repeated exposure.

May be fatal if swallowed and enters airways

Extremely Flammable Aerosol

Contains gas under pressure; may explode if heated



Appearance Clear

Physical state Aerosol

Odor Solvent

# **Precautionary Statements - Prevention**

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood Wear protective gloves/eye protection/face protection/protective clothing Wash face, hands and any exposed skin thoroughly after handling. Do not breathe dust/fume/gas/mist/vapors/spray. Use only outdoors or in a well-ventilated area Keep away from heat/sparks/open flames/hot surfaces.-No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use

## **Precautionary Statements - Response**

If exposed or concerned: Get medical advice/attention. Specific treatment (see first aid on this label) IF ON SKIN: Wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention Take off contaminated clothing and wash before reuse IF INHALED : Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell IF SWALLOWED: Immediately call a poison center/doctor Do NOT induce vomiting.

## F02607 - S-206 SUPER SILICONE SPRAY

# Precautionary Statements - Storage

Store locked up Store in a well-ventilated place. Keep container tightly closed. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F

#### **Precautionary Statements - Disposal** Dispose of contents/container to an approved waste disposal plant

## Hazards not otherwise classified (HNOC)

None

## Other information

0% of the mixture consists of ingredient(s) of unknown toxicity.

## 3. COMPOSITION/INFORMATION ON INGREDIENTS

CAS # 64742-49-0, COMMERCIAL HEXANES, MAY BE SUBSTITUTED FOR CAS #110-54-3.

Chemical Name	CAS-No	Weight %*
1,1-DIFLUOROETHANE	75-37-6	50-60
DIMETHYLETHER	115-10-6	30-40
HEXANE	110-54-3	10-20
DIMETHYL POLYSILOXANE	63148-62-9	1-10

\*The exact percentage (concentration) of composition has been withheld as a trade secret.

# 4. FIRST AID MEASURES

## First aid measures for different exposure routes

General advice	Avoid contact with eyes, skin, and clothing. Avoid breathing vapors, mist, or gas.	
Eye contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If symptoms persist, call a physician.	
Skin contact	Rinse immediately with plenty of water for 15 minutes and seek medical advice if skin irritation persists.	
Inhalation	Move to fresh air. If breathing is difficult, give oxygen. Artificial respiration and/or oxygen may be necessary. If breathing has stopped, contact emergency medical services immediately. If symptoms persist, call a physician.	
Ingestion	Do NOT induce vomiting. Call a physician immediately. Never give anything by mouth to an unconscious person. Risk of product entering the lungs on vomiting after ingestion.	
Most important symptoms/effects, acute and delayed		
Main Symptoms	Causes skin irritation. May cause eye and respiratory irritation. Harmful I if swallowed and enters airways.	
Indication of immediate medical attention and special treatment needed, if necessary		
Notes to physician	Treat symptomatically.	
5. FIRE-FIGHTING MEASURES		

#### Suitable Extinguishing Media

Water fog. Carbon Dioxide (CO2), Foam, Dry Chemical. Cool Tanks/ containers with water spray.

Unsuitable Extinguishing Media Do not use a solid water stream as it may scatter and spread fire.

#### Specific hazards arising from the chemical

Keep product and empty container away from heat and sources of ignition. Extremely Flammable / Flammable.

Explosion Data Sensitivity to Mechanical Impact none. Sensitivity to Static Discharge Yes.

## **Protective Equipment and Precautions for Firefighters**

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Use shielding to protect fire-fighters from bursting containers.

## 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures		
Personal precautions	Use with adequate ventiliation to keep the exposure levels below the OELS.	
Environmental precautions		
Environmental precautions	Prevent further leakage or spillage if safe to do so. Do not allow material to contaminate ground water system. Prevent product from entering drains. Do not flush into surface water or sanitary sewer system. Should not be released into the environment .	
Methods and materials for containment and cleaning up		
Methods for Containment	Absorb or cover with dry earth, sand or other non-combustible material and transfer to containers Prevent further leakage or spillage if safe to do so.	
Methods for cleaning up	Contain liquid and collect with an inter, non-combustible material. Use personal protective equipment. Dam up. Cover liquid spill with sand, earth, or other noncombustible absorbent material. Take up mechanically and collect in suitable container for disposal. Clean contaminated surface thoroughly.	

### 7. HANDLING AND STORAGE

## Precautions for safe handling

Advice on safe handling Avoid contact with eyes. Avoid breathing vapors or mists. Contents under pressure. Do not puncture or incinerate cans. Do not stick pin or any other sharp object into opening on top of can. Avoid skin contact. Use with adequate ventilation. Keep container away from heat, flames, and all other sources of ignition. Keep can away from all sources of electricity such as electric motors and batteries. Do not spray on hot surfaces.

Conditions for safe storage, including any incompatibilities

Technical measures/Storage	Keep container tightly closed in a dry and well-ventilated place. Keep away from open
conditions	flames, hot surfaces, and sources of ignition. Keep in properly labeled containers. Keep out
	of the reach of children. Store locked up.

#### Incompatible products Strong acids, alkalis, oxidizing agents.

1

Aerosol Level

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
1,1-DIFLUOROETHANE 75-37-6	TWA 1000 PPM 8 hours	-	-
		TH// 400 DDM	
DIMETHYLETHER	STEL: 500 PPM	TWX: 400 PPM	IDLH: 1900 PPM (10 % LEL)
115-10-6	TWA: 400PPM	TWA: 1200 mg/m <sup>3</sup>	
HEXANE	TWA: 50 ppm	TWA: 500 ppm	IDLH: 1100 ppm
110-54-3	Skin - potential significant	TWA: 1800 mg/m <sup>3</sup>	TWA: 50 ppm
	contribution to overall exposure	(vacated) TWA: 50 ppm	TWA: 180 mg/m <sup>3</sup>
	by the cutaneous route	(vacated) TWA: 180 mg/m <sup>3</sup>	
CGIH: (American Conference of	Governmental Industrial Hygienists,	)	
SHA: (Occupational Safety & Hea	alth Administration)		
IIOSH IDLH: Immediately Dangel			
ther Exposure Guidelines	Vacated limits revoked by the 0	Court of Appeals decision in A	FL-CIO v. OSHA, 965 F.2d 9
•			
	(11th Cir., 1992).		
	(11th Cir., 1992).		
xposure controls	(11th Cir., 1992).		
xposure controls ngineering Measures	(11th Cir., 1992). Showers, eyewash stations, ar	nd ventilation systems.	
ngineering Measures			
ngineering Measures	Showers, eyewash stations, an	pment	
ngineering Measures ndividual protection measures, Eye/Face Protection	Showers, eyewash stations, an such as personal protective equip Safety glasses with side-shield	pment s.	
ngineering Measures	Showers, eyewash stations, an such as personal protective equi	pment s.	
ngineering Measures ndividual protection measures, Eye/Face Protection	Showers, eyewash stations, an such as personal protective equip Safety glasses with side-shield Chemical resistant apron. Prote If exposure limits are exceeded respiratory protection should be required for high airborne conta	pment ls. ective gloves. d or irritation is experienced, N e worn. Positive-pressure sup aminant concentrations. Resp	plied air respirators may be
ngineering Measures ndividual protection measures, Eye/Face Protection Skin and body protection	Showers, eyewash stations, an such as personal protective equip Safety glasses with side-shield Chemical resistant apron. Prote If exposure limits are exceeded respiratory protection should be	pment ls. ective gloves. d or irritation is experienced, N e worn. Positive-pressure sup aminant concentrations. Resp	plied air respirators may be

# 9. PHYSICAL AND CHEMICAL PROPERTIES

# Physical and chemical properties

Physical state Appearance Color	Aerosol Clear Clear	Odor Odor Threshold	Solvent
<u>Property</u> pH Melting/freezing point Boiling point/boiling range	<u>Values</u> No information available No information available	Remarks • Methods	
Flash Point Evaporation rate Flammability (solid, gas) Flammability Limits in Air upper flammability limit lower flammability limit	-50 °C / -58 °F No information available No information available	(based on components)	
Vapor pressure Vapor density Specific Gravity Water solubility Partition coefficient: n-octanol/wate Autoignition temperature Decomposition temperature Viscosity Explosive properties	0.975 Practically insoluble <b>F</b> No information available No information available	Not applicable	

#### **Other information**

VOC Content(%)
MIR Value
MIR Coating Category

45.17 0.45 MRC - Mold Release Coating < 1.10 MIR

# **10. STABILITY AND REACTIVITY**

Reactivity No data available

#### **Chemical stability**

Stable under recommended storage conditions.

#### Possibility of hazardous reactions

None under normal processing.

#### **Conditions to Avoid**

Extremes of temperature and direct sunlight.

#### **Incompatible Materials**

Strong acids, alkalis, oxidizing agents.

## Hazardous Decomposition Products

Carbon oxides , Hydrocarbons, Fumes.

# **11. TOXICOLOGICAL INFORMATION**

### Information on likely routes of exposure

#### **Product Information**

Inhalation	Avoid inhaling vapors or mists. May cause irritation to respiratory tract. May cause drowsiness and dizziness.
Eye contact	May be irritating to the eyes.
Skin contact	Causes skin irritation. Prolonged skin contact may defat the skin and produce dermatitis.
Ingestion	Harmful and may be fatal if swallowed and enters airways.

#### Component Information

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
DIMETHYLETHER 115-10-6	-	-	= 308.5 mg/L (Rat)4 h
HEXANE 110-54-3	= 25 g/kg (Rat)	= 3000 mg/kg (Rabbit)	= 48000 ppm (Rat)4 h

#### Information on toxicological effects

Symptoms

May cause eye, skin, and respiratory irritation. May cause drowsiness and dizziness. Harmful and may be fatal if swallowed and enters airways.

## Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation	Irritating to skin.
Eye damage/irritation	May cause eye irritation.
Irritation	Causes eye irritation. May cause skin and respiratory irritation.
Sensitization	No information available.
Germ Cell Mutagenicity	Not a germ cell mutagen.
Carcinogenicity	There are no carcinogenic chemicals in this product.

ACGIH: (American Conference of G	Sovernmental Industrial Hygienists)				
A2 - Suspected Human Carcinogen					
A3 - Animal Carcinogen					
IARC: (International Agency for Res	earch on Cancer)				
Group 1 - Carcinogenic to Humans					
Group 2B - Possibly Carcinogenic to F					
Group 3 - Not Classifiable as to Carcir	• •				
Group 2A - Probably Carcinogenic to I	Humans				
NTP: (National Toxicity Program)					
	Anticipated to be a Human Carcinogen				
OSHA: (Occupational Safety & Heal	th Administration)				
X - Present					
Reproductive toxicity	This product contains a chemical(s) which is a known or suspected reproductive hazard .				
Specific target organ systemic	May cause drowsiness and dizziness. May cause respiratory irritation.				
toxicity (single exposure)					
Specific target organ systemic	May cause damage to target organs listed below through prolonged or repeated exposure.				
toxicity (repeated exposure)					
Chronic toxicity	Intentional misuse by deliberately concentrating and inhaling contents may be harmful or				
······································	fatal. Chronic hydrocarbon abuse has been associated with irregular heart rhythms and				
	potential cardiac arrest.				
Target Organ Effects	Eyes, Skin, Respiratory System, and Central Nervous System.				
	May be fatal if swallowed and enters airways.				
Aspiration hazard	iviay be latar in swanowed and enters an ways.				

## Numerical measures of toxicity - Product Information

Unknown Acute Toxicity	0% of the mixture consists of ingredient(s) of unknown toxicity.
The following values are calculated	based on chapter 3.1 of the GHS document
ATEmix (oral)	23428 mg/kg
ATEmix (dermal)	10898 mg/kg
ATEmix (inhalation-gas)	78604 mg/l
ATEmix (inhalation-dust/mist)	94.7 mg/l
ATEmix (inhalation-vapor)	174368 mg/l

# **12. ECOLOGICAL INFORMATION**

## **Ecotoxicity**

Chemical Name	ne Toxicity to algae Toxicity to fish		Toxicity to microorganisms	Toxicity to daphnia and other aquatic invertebrates
HEXANE 110-54-3	-	2.1 - 2.98 mg/L LC50 Pimephales promelas 96h flow-through	-	-
DIMETHYL POLYSILOXANE 63148-62-9	-	-	-	>10,000mg/L EC50 Daaphina magnma 48 h

# Persistence and degradability

## **Bioaccumulation**

Chemical Name	log Pow
DIMETHYLETHER	-0.18
115-10-6	

#### Other adverse effects

No information available

# 13. DISPOSAL CONSIDERATIONS

## Waste treatment

Waste Disposal Methods	This material, as supplied, is a hazardous waste according to federal regulations (40 CFR 261). Dispose of in accordance with federal, state, and local regulations.
Contaminated packaging	Do not re-use empty containers.

# **14. TRANSPORT INFORMATION**

DOT Ground	CONSUMER COMMODITY ORM-D
	or
	LIMITED QUANTITY

ΙΑΤΑ	UN1950, AEROSOLS, FLAMMABLE, 2.1, LTD.QTY.
IMDG	UN1950, AEROSOLS, 2.1, LTD.QTY

## **15. REGULATORY INFORMATION**

## International Inventories

Chemical Name	TSCA	DSL/NDSL	EINECS/ELI NCS	ENCS	IECSC	KECL	PICCS	AICS
1,1-DIFLUOROETHA NE	Х	X	Х	Х	Х	Х	Х	Х
DIMETHYLETHER	Х	X	Х	Х	Х	Х	Х	Х
HEXANE	Х	X	Х	Х	Х	Х	Х	Х
DIMETHYL POLYSILOXANE	Х	X	Not listed	х	Х	Х	Х	Х

## Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

CHINA - China Inventory of Existing Chemical Substances

**KECL** - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

## U.S. Federal Regulations

#### <u>SARA 313</u>

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does contain a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372:

Chemical Name	CAS-No	Weight %*	SARA 313 - Threshold Values %	
HEXANE - 110-54-3	110-54-3	10-20	1.0	

Yes Yes

#### SARA 311/312 Hazard Categories Acute Health Hazard

Acute Health Hazard	
Chronic Health Star Hazard	

Fire Hazard	Yes
Sudden Release of Pressure Hazard	Yes
Reactive Hazard	no

## **Clean Water Act**

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42).

## **CERCLA**

This material, as supplied, does contain substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302):

	Chemical Name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ
Γ	HEXANE	5000 lb		RQ 5000 lb final RQ
	110-54-3			RQ 2270 kg final RQ

## U.S. State Regulations

#### California Proposition 65

This product contains the following Proposition 65 chemicals:



This product can expose you to chemicals including those listed below, which is [are] known to the State of California to cause cancer, birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

Chemical Name	California Prop. 65
HEXANE - 110-54-3	Developmental, Reproductive (Male) 10-20%

## U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
1,1-DIFLUOROETHANE 75-37-6	Х	X	
DIMETHYLETHER 115-10-6	Х	X	X
HEXANE 110-54-3	Х	X	X

EPA Pesticide Registration Number Not applicable

#### <u>Canada</u>

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all the information required by the CPR.

#### WHMIS Hazard Class

A Compressed gases B5 Flammable aerosol D2B Toxic materials

# **16. OTHER INFORMATION**

<u>NFPA</u>	Health Hazard 2	Flammability 4	Instability 0	Physical and chemical hazards
HMIS_ Chronic Hazard Star Leg	Health Hazard 2* end Chronic He damage	Flammability 4 alth Star Hazard Repeated	Physical Hazard 1 or prolonged exposure may cau	Personal protection B

Issuing date	05-Dec-2017
Revision Date	02-Jan-2018
Revision Note	

#### Disclaimer

The information provided on this SDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

End of Safety Data Sheet