SAFETY DATA SHEET.

Issuing date 01-Dec-2017 Revision Date 04-Jan-2018 Version 1.02

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product identifier

Product name SB-128 SYNERGY BLEND SILICONE

Recommended use of the chemical

and restrictions on use

Product code F03016

Product Type Extremely Flammable Aerosol

Synonyms None

Supplier's details

Recommended Use Mold Release Agent.
Uses advised against No information available

Manufacturer:

Plastic Process Equipment,Inc. 8303 Corporate Park Dr. Macedonia, Ohio 44056 Phone: 800-321-0562

Emergency telephone number

Chemical Emergency Phone

Number

1-800-262-8200 ID 1195 (UNITED STATES)

2. HAZARDS IDENTIFICATION

Classification

Skin corrosion/irritation	Category 2
Reproductive Toxicity	Category 2
Specific target organ toxicity (single exposure)	Category 3
Specific target organ toxicity (repeated exposure)	Category 2
Aspiration toxicity	Category 1
Flammable aerosols	Category 1
Gases under pressure	Compressed Gas

GHS Label elements, including precautionary statements

Emergency Overview

DANGER

Hazard Statements

Causes skin irritation

Suspected of damaging fertility or the unborn child

May cause respiratory irritation. May cause drowsiness or dizziness.

May cause damage to organs (Eyes, Skin, Respiratory System, Central Nervous System, and Peripheral Nervous System)

through prolonged or repeated exposure.

May be fatal if swallowed and enters airways

Extremely Flammable Aerosol

Contains gas under pressure; may explode if heated



Appearance Clear Physical state Aerosol Odor Solvent

Precautionary Statements - Prevention

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood

Wear protective gloves/eye protection/face protection/protective clothing

Wash face, hands and any exposed skin thoroughly after handling.

Do not breathe dust/fume/gas/mist/vapors/spray.

Use only outdoors or in a well-ventilated area

Keep away from heat/sparks/open flames/hot surfaces.-No smoking.

Do not spray on an open flame or other ignition source.

Pressurized container: Do not pierce or burn, even after use

Precautionary Statements - Response

If exposed or concerned: Get medical advice/attention.

Specific treatment is urgent (see first aid on this label)

IF ON SKIN: Wash with plenty of soap and water.

If skin irritation occurs: Get medical advice/attention

Take off contaminated clothing and wash before reuse

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Call a POISON CENTER or doctor/physician if you feel unwell

IF SWALLOWED: Immediately call a poison center/doctor

Do NOT induce vomiting.

Precautionary Statements - Storage

Store locked up

Store in a well-ventilated place. Keep container tightly closed.

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

None

Other information

0% of the mixture consists of ingredient(s) of unknown toxicity.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS-No	Weight %*
1,1-DIFLUOROETHANE	75-37-6	50-60
DIMETHYLETHER	115-10-6	50-60
HEXANE	110-54-3	10-20
POLYDIMETHYLSILOXANE	63148-62-9	1-10

^{*}The exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

First aid measures for different exposure routes

General advice Avoid contact with eyes, skin, and clothing. Avoid breathing vapors, mist, or gas.

Eye contact Immediately flush with plenty of water for at least 15 minutes. After initial flushing, remove

any contact lenses and continue flushing. Seek immediate medical attention/advice. If

symptoms persist, call a physician.

Skin contact Rinse immediately with plenty of water for 15 minutes and seek medical advice if skin

irritation persists.

Inhalation Move to fresh air. If breathing is difficult, give oxygen. Artificial respiration and/or oxygen

may be necessary. If breathing has stopped, contact emergency medical services

immediately.

Ingestion Do NOT induce vomiting. Call a physician or Poison Control Center immediately. Never

give anything by mouth to an unconscious person. Risk of product entering the lungs on

vomiting after ingestion.

Most important symptoms/effects, acute and delayed

Main Symptoms Causes skin irritation. May cause eye and respiratory irritation. Harmful I if swallowed and

enters airways.

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Water fog. Carbon Dioxide (CO2), Foam, Dry Chemical. Cool Tanks/ containers with water spray.

Unsuitable Extinguishing Media Do not use a solid water stream as it may scatter and spread fire.

Specific hazards arising from the chemical

Extremely Flammable / Flammable. Keep product and empty container away from heat and sources of ignition.

Explosion Data

Sensitivity to Mechanical Impact none.
Sensitivity to Static Discharge Yes.

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Use shielding to protect fire-fighters from bursting containers.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions

Use with adequate ventiliation to keep the exposure levels below the OELS.

Environmental precautions

Environmental precautions Prevent further leakage or spillage if safe to do so. Do not allow material to contaminate

ground water system. Prevent product from entering drains. Do not flush into surface water

or sanitary sewer system. Should not be released into the environment .

Methods and materials for containment and cleaning up

Methods for Containment Absorb or cover with dry earth, sand or other non-combustible material and transfer to

containers Prevent further leakage or spillage if safe to do so.

Methods for cleaning up Soak up with inert absorbent material. Contain liquid and collect with an inter,

non-combustible material. Pick up and transfer to properly labeled containers. Clean contaminated surface thoroughly . After cleaning, flush away traces with water. Prevent product from entering drains. Take precautionary measures against static discharges.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling Avoid contact with eyes. Avoid breathing vapors or mists. Contents under pressure. Do not

puncture or incinerate cans. Do not stick pin or any other sharp object into opening on top of can. Avoid skin contact. Use with adequate ventilation. Keep container away from heat, flames, and all other sources of ignition . Keep can away from all sources of electricity such

as electric motors and batteries. Do not spray on hot surfaces.

Conditions for safe storage, including any incompatibilities

Technical measures/Storage

conditions

Keep container tightly closed in a dry and well-ventilated place. Keep away from open flames, hot surfaces, and sources of ignition. Keep in properly labeled containers. Keep out

of the reach of children. Store locked up.

Incompatible products Strong acids, alkalis, oxidizing agents.

Aerosol Level 1

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
1,1-DIFLUOROETHANE	TWA 1000 PPM 8 hours	-	-
75-37-6			
DIMETHYLETHER	STEL: 500 PPM	TWX: 400 PPM	IDLH: 1900 PPM (10 % LEL)
115-10-6	TWA: 400PPM	TWA: 1200 mg/m ³	·
HEXANE	TWA: 50 ppm	TWA: 500 ppm	IDLH: 1100 ppm
110-54-3	Skin - potential significant	TWA: 1800 mg/m ³	TWA: 50 ppm
	contribution to overall exposure	(vacated) TWA: 50 ppm	TWA: 180 mg/m ³
	by the cutaneous route	(vacated) TWA: 180 mg/m ³	

ACGIH: (American Conference of Governmental Industrial Hygienists)

OSHA: (Occupational Safety & Health Administration) NIOSH IDLH: Immediately Dangerous to Life or Health

Other Exposure Guidelines Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962

(11th Cir., 1992).

Exposure controls

Engineering Measures Showers, eyewash stations, and ventilation systems.

Individual protection measures, such as personal protective equipment

Eye/Face Protection Safety glasses with side-shields.

Skin and body protection Chemical resistant apron. Protective gloves.

Respiratory protection If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved

respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be

Not applicable

provided in accordance with current local regulations.

Hygiene measuresHandle in accordance with good industrial hygiene and safety practice.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical and chemical properties

Physical state Aerosol Appearance Clear

Appearance Clear Odor Solvent

Color Clear Odor Threshold

<u>Property</u> <u>Values</u> <u>Remarks • Methods</u>

pH No information available

Melting/freezing point No information available

Boiling point/boiling range

Flash Point -50 °C / -58 °F Based on propellant

Evaporation rate No information available Flammability (solid, gas) No information available

Flammability (solid, gas) No information as Flammability Limits in Air

upper flammability limit lower flammability limit

Vapor pressure Vapor density

Specific Gravity 0.795 Water solubility None

Partition coefficient: n-octanol/water

Autoignition temperature No information available

Decomposition temperature

Viscosity No information available

Explosive properties

Other information

VOC Content(%) 45.93 **MIR Value** 0.46

MIR Coating Category MRC - Mold Release Coating < 1.10 MIR

10. STABILITY AND REACTIVITY

Reactivity

No data available

Chemical stability

Stable under recommended storage conditions.

Possibility of hazardous reactions

None under normal processing.

Conditions to Avoid

Extremes of temperature and direct sunlight.

Incompatible Materials

Strong acids, alkalis, oxidizing agents.

Hazardous Decomposition Products

Carbon oxides, Hydrocarbons, Fumes.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information

Inhalation Avoid inhaling vapors or mists. May cause irritation to respiratory tract. May cause

drowsiness and dizziness.

Eye contact May be irritating to the eyes.

Skin contact Irritating to skin. Prolonged contact may defat the skin and produce dermatitis.

Ingestion Harmful and may be fatal if swallowed and enters airways.

Component Information

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
DIMETHYLETHER	-	-	= 308.5 mg/L (Rat) 4 h
115-10-6			
HEXANE	= 25 g/kg (Rat)	= 3000 mg/kg (Rabbit)	= 48000 ppm (Rat) 4 h
110-54-3			
POLYDIMETHYLSILOXANE	> 24 g/kg (Rat)	=	-
63148-62-9			

Information on toxicological effects

Symptoms May cause eye, skin, and respiratory irritation. May cause drowsiness and dizziness.

Harmful and may be fatal if swallowed and enters airways.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritationCauses skin irritation.Eye damage/irritationIrritating to eyes.

Irritation Causes eye irritation. May cause skin and respiratory irritation.

Sensitization No information available.

Germ Cell Mutagenicity Not a germ cell mutagen.

Carcinogenicity There are no carcinogenic chemicals in this product.

ACGIH: (American Conference of Governmental Industrial Hygienists)

A2 - Suspected Human Carcinogen

IARC: (International Agency for Research on Cancer)

Group 1 - Carcinogenic to Humans

Group 2B - Possibly Carcinogenic to Humans

Group 3 - Not Classifiable as to Carcinogenicity in Humans

NTP: (National Toxicity Program)

Reasonably Anticipated - Reasonably Anticipated to be a Human Carcinogen

OSHA: (Occupational Safety & Health Administration)

X - Present

Reproductive toxicity

Specific target organ systemic toxicity (single exposure) Specific target organ systemic

May cause drowsiness and dizziness. May cause respiratory irritation.

toxicity (repeated exposure)

Chronic toxicity

Target Organ Effects

May cause damage to target organs listed below through prolonged or repeated exposure.

Product is or contains a chemical which is a known or suspected reproductive hazard.

Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal. Chronic hydrocarbon abuse has been associated with irregular heart rhythms and potential cardiac arrest. May cause adverse liver effects. Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal. Chronic hydrocarbon abuse has been associated with irregular heart rhythms and potential cardiac arrest.

Eyes, Skin, Respiratory System, and Central Nervous System.

Aspiration hazard May be fatal if swallowed and enters airways.

Numerical measures of toxicity - Product Information

Unknown Acute Toxicity 0% of the mixture consists of ingredient(s) of unknown toxicity.

The following values are calculated based on chapter 3.1 of the GHS document .

ATEmix (oral) 23428 mg/kg 10898 mg/kg ATEmix (dermal) ATEmix (inhalation-gas) 78604 mg/l ATEmix (inhalation-dust/mist) 94.7 mg/l ATEmix (inhalation-vapor) 174368 mg/l

12. ECOLOGICAL INFORMATION

Ecotoxicity

Chemical Name	Toxicity to algae	Toxicity to fish	Toxicity to microorganisms	Toxicity to daphnia and other aquatic invertebrates
HEXANE	-	2.1 - 2.98 mg/L LC50	-	-
110-54-3		Pimephales promelas 96h		
		flow-through		

Persistence and degradability

Bioaccumulation

Chemical Name	log Pow
DIMETHYLETHER	-0.18
115-10-6	

No information available Other adverse effects

13. DISPOSAL CONSIDERATIONS

Waste treatment

Waste Disposal Methods This material, as supplied, is a hazardous waste according to federal regulations (40 CFR

261). Dispose of in accordance with federal, state, and local regulations.

Contaminated packaging D

Do not re-use empty containers.

14. TRANSPORT INFORMATION

DOT Ground CONSUMER COMMODITY ORM-D

or

LIMITED QUANTITY

IATA UN1950, AEROSOLS, FLAMMABLE, 2.1, LTD.QTY.

IMDG UN1950, AEROSOLS, 2.1, LTD.QTY

15. REGULATORY INFORMATION

International Inventories

Chemical Name	TSCA	DSL/NDSL	EINECS/ELI NCS	ENCS	IECSC	KECL	PICCS	AICS
1,1-DIFLUOROETHA NE	Х	Х	Х	Х	Х	Х	Х	Х
DIMETHYLETHER	Х	Х	X	X	X	X	X	Х
HEXANE	X	Х	Х	X	Х	Х	X	Х
POLYDIMETHYLSILO XANE	Х	Х	Not listed	Not listed	X	Х	Х	Х

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

CHINA - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

U.S. Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does contain a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372:

Chemical Name	CAS-No	Weight %*	SARA 313 - Threshold Values %
HEXANE - 110-54-3	110-54-3	10-20	1.0

SARA 311/312 Hazard Categories

TOTO TIONE TIME OUT OF OTHER	
Acute Health Hazard	Yes
Chronic Health Star Hazard	Yes
Fire Hazard	Yes
Sudden Release of Pressure Hazard	Yes

Reactive Hazard no

Clean Water Act

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42).

CERCLA

This material, as supplied, does contain substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302):

Chemical Name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ
HEXANE 110-54-3	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ

U.S. State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals:



This product can expose you to chemicals including those listed below, which is [are] known to the State of California to cause cancer, birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

Chemical Name	California Prop. 65
HEXANE - 110-54-3	Developmental , Reproductive (Male) 10-20%

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
1,1-DIFLUOROETHANE	X	X	
75-37-6			
DIMETHYLETHER	X	X	X
115-10-6			
HEXANE	X	X	X
110-54-3			

EPA Pesticide Registration Number Not applicable

Canada

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all the information required by the CPR.

WHMIS Hazard Class

A Compressed gases B5 Flammable aerosol D2B Toxic materials

16. OTHER INFORMATION

F03016 - SB-128 SYNERGY BLEND SILICONE

Revision Date 04-Jan-2018

NFPA Health Hazard 2 Flammability 4 Instability 0 Physical and chemical

hazards -

HMIS Health Hazard 2* Flammability 4 Physical Hazard 1 Personal protection B

Chronic Hazard Star Legend Chronic Health Star Hazard Repeated or prolonged exposure may cause central nervous system

damage

Issuing date01-Dec-2017Revision Date04-Jan-2018

Revision Note

Disclaimer

The information provided on this SDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

End of Safety Data Sheet
