# SAFETY DATA SHEET.

Issuing date 14-Mar-2017 Revision Date 28-Mar-2018 Version 1

# 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product identifier

Product name SMP-12 SEALSAFE

Recommended use of the chemical

and restrictions on use

Product code F03836

Product Type Extremely Flammable Aerosol

Synonyms None

Supplier's details

Recommended Use Metal protectant.
Uses advised against No information available

Manufacturer:

Plastic Process Equipment,Inc. 8303 Corporate Park Dr. Macedonia, Ohio 44056 Phone: 800-321-0562

Emergency telephone number

**Chemical Emergency Phone** 

Number

(1-800-262-8200 ID 1195 (UNITED STATES)

## 2. HAZARDS IDENTIFICATION

#### Classification

Acute toxicity - Inhalation (Dusts/Mists)	Category 4
Serious eye damage/eye irritation	Category 2A
Reproductive Toxicity	Category 2
Specific target organ toxicity (repeated exposure)	Category 2
Aspiration toxicity	Category 1
Flammable aerosols	Category 1
Gases under pressure	Compressed Gas

# GHS Label elements, including precautionary statements

#### **Emergency Overview**

#### DANGER

#### Hazard Statements

Harmful if inhaled

Causes serious eye irritation

Suspected of damaging fertility or the unborn child

May cause damage to organs (Central Nervous System, Respiratory System, Eyes, Skin, Kidney, Blood, Bone Marrow, and Liver) through prolonged or repeated exposure.

May be fatal if swallowed and enters airways

Extremely Flammable Aerosol

Contains gas under pressure; may explode if heated



Appearance Opaque Physical state Aerosol Odor Solvent

# **Precautionary Statements - Prevention**

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Wear protective gloves/protective clothing/eye protection/face protection.

Use only outdoors or in a well-ventilated area

Wash face, hands and any exposed skin thoroughly after handling.

Do not breathe dust/fume/gas/mist/vapors/spray.

Keep away from heat/sparks/open flames/hot surfaces.-No smoking.

Do not spray on an open flame or other ignition source.

Pressurized container: Do not pierce or burn, even after use

# **Precautionary Statements - Response**

If exposed or concerned: Get medical advice/attention.

IF IN EYES:Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If eye irritation persists: Get medical advice/attention

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Call a POISON CENTER or doctor/physician if you feel unwell

IF SWALLOWED: Immediately call a poison center/doctor

Do NOT induce vomiting.

# **Precautionary Statements - Storage**

Store locked up

Protect from sunlight. Store in a well-ventilated place Do not expose to temperatures exceeding 122°F (50°C)

# **Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant

### Hazards not otherwise classified (HNOC)

None

### Other information

0% of the mixture consists of ingredient(s) of unknown toxicity.

# 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS-No	Weight %*
MEDIUM POLYALPHAOLEFINS	68037-01-04	30-40
1,1-DIFLUOROETHANE	75-37-6	10-20
NAPHTHENIC OIL, SEVERLY HYDROT	64742-52-5	10-20
DIMETHYLETHER	115-10-6	10-20
TOLUENE	108-88-3	1-10
METHYLATED SILICA	68611-44-9	1-10
XYLENE	1330-20-7	<0.1
ETHYL BENZENE	100-41-4	<0.01
BENZENE	71-43-2	<0.01
NAPHTHALENE	91-20-3	<0.001

<sup>\*</sup>The exact percentage (concentration) of composition has been withheld as a trade secret.

# 4. FIRST AID MEASURES

#### First aid measures for different exposure routes

General advice Avoid contact with eyes, skin, and clothing. Avoid breathing vapors, mist, or gas.

**Eye contact** Immediately flush with plenty of water for at least 15 minutes. After initial flushing, remove

any contact lenses and continue flushing. If eye irritation persists, consult a doctor.

**Skin contact**Wash off with soap and plenty of water. Remove and wash contaminated clothing before

re-use. If skin irritation persists, call a physician.

**Inhalation** Move to fresh air. If not breathing, give artificial respiration. If breathing has stopped,

contact emergency medical services immediately.

Ingestion Call a physician or Poison Control Center immediately. Do NOT induce vomiting. Never

give anything by mouth to an unconscious person. Risk of product entering the lungs on

vomiting after ingestion.

# Most important symptoms/effects, acute and delayed

Main Symptoms Harmful if inhaled. Causes serious eye irritation. Suspected of damaging fertility or the

unborn child. May cause damage to organs through prolonged or repeated exposure. May

be fatal if swallowed and enters airways.

#### Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician Treat symptomatically.

# 5. FIRE-FIGHTING MEASURES

#### Suitable Extinguishing Media

Water fog.Dry chemical. Foam.Carbon dioxide (CO2). Cool containers/tanks with water spray.

**Unsuitable Extinguishing Media** Keep away from sources of ignition - No smoking. Cool containers / tanks with water spray. Remove all sources of ignition.

### Specific hazards arising from the chemical

Extremely Flammable / Flammable. Keep product and empty container away from heat and sources of ignition. Risk of ignition. In the event of fire and/or explosion do not breathe fumes. In the event of fire, cool tanks with water spray.

#### **Explosion Data**

**Sensitivity to Mechanical Impact** none. **Sensitivity to Static Discharge** Yes.

#### **Protective Equipment and Precautions for Firefighters**

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

### 6. ACCIDENTAL RELEASE MEASURES

### Personal precautions, protective equipment and emergency procedures

handling advice and personal protective equipment recommendations.

**Environmental precautions** 

Environmental precautions Vapors can accumulate in low areas. Do not allow material to contaminate ground water

system. Report spills as required by local and federal regulations. Do not flush into surface

water or sanitary sewer system. Should not be released into the environment.

# Methods and materials for containment and cleaning up

Methods for Containment Absorb with earth, sand or other non-combustible material and transfer to containers for

later disposal. Prevent further leakage or spillage if safe to do so. Do not allow material to

contaminate ground water system. Prevent product from entering drains.

Methods for cleaning up Soak up with inert absorbent material. Contain liquid and collect with an inter,

non-combustible material. Pick up and transfer to properly labeled containers. Clean contaminated surface thoroughly . After cleaning, flush away traces with water. Prevent product from entering drains. Take precautionary measures against static discharges.

# 7. HANDLING AND STORAGE

#### Precautions for safe handling

Advice on safe handling Avoid breathing vapors or mists. Avoid contact with skin, eyes and clothing. Keep away

from open flames, hot surfaces and sources of ignition. Contents under pressure. Do not puncture or incinerate cans. Handle in accordance with good industrial hygiene and safety

practice. Take precautionary measures against static discharges.

## Conditions for safe storage, including any incompatibilities

\_\_\_\_\_

Technical measures/Storage

conditions

Keep container tightly closed in a dry and well-ventilated place. Keep away from open flames, hot surfaces, and sources of ignition. Keep in properly labeled containers. Keep out

of the reach of children. Store locked up.

Incompatible products

Strong acids, alkalis, oxidizing agents.

**Aerosol Level** 

1

# 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

## Control parameters

**Exposure Guidelines** 

Exposure Guidelliles	•		
Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
1,1-DIFLUOROETHANE 75-37-6	TWA 1000 PPM 8 hours	-	-
DIMETHYLETHER 115-10-6	STEL: 500 PPM TWA: 400PPM	TWX: 400 PPM TWA: 1200 mg/m <sup>3</sup>	IDLH: 1900 PPM (10 % LEL)
TOLUENE 108-88-3	TWA: 20 ppm	TWA: 200 ppm (vacated) TWA: 100 ppm (vacated) TWA: 375 mg/m³ (vacated) STEL: 150 ppm (vacated) STEL: 560 mg/m³ Ceiling: 300 ppm	IDLH: 500 ppm TWA: 100 ppm TWA: 375 mg/m³ STEL: 150 ppm STEL: 560 mg/m³
XYLENE 1330-20-7	STEL: 150 ppm TWA: 100 ppm	TWA: 100 ppm TWA: 435 mg/m³ (vacated) TWA: 100 ppm (vacated) TWA: 435 mg/m³ (vacated) STEL: 150 ppm (vacated) STEL: 655 mg/m³	Not Established
ETHYL BENZENE 100-41-4	TWA: 20 ppm	TWA: 100 ppm TWA: 435 mg/m³ (vacated) TWA: 100 ppm (vacated) TWA: 435 mg/m³ (vacated) STEL: 125 ppm (vacated) STEL: 545 mg/m³	IDLH: 800 ppm TWA: 100 ppm TWA: 435 mg/m³ STEL: 125 ppm STEL: 545 mg/m³
BENZENE 71-43-2	STEL: 2.5 ppm TWA: 0.5 ppm Skin - potential significant contribution to overall exposure by the cutaneous route	TWA: 10 ppm applies to industry segments exempt from the benzene standard at 29 CFR 1910.1028 TWA: 1 ppm (vacated) TWA: 10 ppm unless specified in 1910.1028 (vacated) STEL: 50 ppm 10 min unless specified in 1910.1028 (vacated) Ceiling: 25 ppm unless specified in 1910.1028 Ceiling: 25 ppm STEL: 5 ppm see 29 CFR 1910.1028	IDLH: 500 ppm TWA: 0.1 ppm STEL: 1 ppm
NAPHTHALENE 91-20-3	TWA: 10 ppm Skin - potential significant contribution to overall exposure by the cutaneous route	TWA: 10 ppm TWA: 50 mg/m³ (vacated) TWA: 10 ppm (vacated) TWA: 50 mg/m³ (vacated) STEL: 15 ppm (vacated) STEL: 75 mg/m³	IDLH: 250 ppm TWA: 10 ppm TWA: 50 mg/m³ STEL: 15 ppm STEL: 75 mg/m³

ACGIH: (American Conference of Governmental Industrial Hygienists)

OSHA: (Occupational Safety & Health Administration) NIOSH IDLH: Immediately Dangerous to Life or Health

Other Exposure Guidelines

Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992).

# **Exposure controls**

**Engineering Measures** Showers

Eyewash stations

Ventilation systems.

Individual protection measures, such as personal protective equipment

**Eye/Face Protection** Safety glasses with side-shields.

Skin and body protection Chemical resistant apron. Protective gloves.

If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved Respiratory protection

> respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be

provided in accordance with current local regulations.

Hygiene measures Handle in accordance with good industrial hygiene and safety practice.

# 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical and chemical properties

Physical state Aerosol

Appearance Opaque Solvent Odor

Color Dark Green **Odor Threshold** 

Property Values Remarks • Methods

No information available Ha Melting/freezing point No information available

Boiling point/boiling range

-50 °C / -58 °F **Flash Point** Based on propellant

No information available **Evaporation rate** Flammability (solid, gas) No information available

Flammability Limits in Air upper flammability limit lower flammability limit

Vapor pressure Vapor density

**Specific Gravity** 0.877 Water solubility None Partition coefficient: n-octanol/water

**Autoignition temperature** 

No information available

**Decomposition temperature** 

No information available **Viscosity** 

**Explosive properties** 

**Other information** 

VOC Content(%) 18.25

# 10. STABILITY AND REACTIVITY

Reactivity

No data available

**Chemical stability** 

Stable under recommended storage conditions.

Possibility of hazardous reactions

None under normal processing.

#### F03836 - SMP-12 SEALSAFE

### **Conditions to Avoid**

Extremes of temperature and direct sunlight.

#### **Incompatible Materials**

Strong acids, alkalis, oxidizing agents.

# **Hazardous Decomposition Products**

Carbon oxides, Hydrocarbons, Fumes.

# 11. TOXICOLOGICAL INFORMATION

## Information on likely routes of exposure

#### **Product Information**

Inhalation Harmful if inhaled.

**Eye contact** Causes serious eye irritation.

**Skin contact** Skin irritation may occur if person excessively exposes product to the skin.

**Ingestion** May be fatal if swallowed and enters airways.

**Component Information** 

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
DIMETHYLETHER	-	-	= 308.5 mg/L (Rat) 4 h
115-10-6			
TOLUENE	= 2600 mg/kg (Rat)	= 12000 mg/kg ( Rabbit )	= 12.5 mg/L (Rat) 4 h
108-88-3			
XYLENE	= 3500 mg/kg (Rat)	> 4350 mg/kg (Rabbit)	= 29.08 mg/L (Rat) 4 h
1330-20-7			
ETHYL BENZENE	= 3500 mg/kg (Rat)	= 15400 mg/kg (Rabbit)	= 17.2 mg/L (Rat) 4 h
100-41-4			
BENZENE	= 810 mg/kg (Rat)	> 8200 mg/kg (Rabbit)	= 44.66 mg/L (Rat) 4 h
71-43-2			
NAPHTHALENE	= 1110 mg/kg (Rat)	= 1120 mg/kg ( Rabbit )	> 340 mg/m³ (Rat) 1 h
91-20-3			

# Information on toxicological effects

Symptoms Harmful if inhaled. Causes serious eye irritation. Suspected of damaging fertility or the

unborn child. May cause damage to organs (listed below) through prolonged or repeated

exposure. May be fatal if swallowed and enters airways.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation Under normal conditions there is no skin irritation. Excessive exposure of product with skin

may cause skin irritation.

Eye damage/irritation

**Sensitization** Not a known sensitizer. **Germ Cell Mutagenicity** Not a germ cell mutagen.

Carcinogenicity The table below indicates whether each agency has evaluated a listed ingredient as a

carcinogen.

Irritating to eyes.

	carcinogen.			
Chemical Name	ACGIH	IARC	NTP	OSHA
TOLUENE	-	Group 3	-	-
108-88-3		-		
XYLENE	-	Group 3	-	-
1330-20-7				
ETHYL BENZENE	A3	Group 2B	-	-
100-41-4				
BENZENE	A1	Group 1	Known	X
71-43-2				

NAPHTHALENE	A3	Group 2B	Reasonably Anticipated	-
91-20-3		-		

IARC: (International Agency for Research on Cancer) Group 3 - Not Classifiable as to Carcinogenicity in Humans

Reproductive toxicity This product contains a chemical(s) which is a known or suspected reproductive hazard.

Specific target organ systemic toxicity (single exposure)

No known effect based on information supplied.

Specific target organ systemic toxicity (repeated exposure) **Chronic toxicity** 

May cause damage to target organs listed below through prolonged and repeated exposure.

Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal. Chronic hydrocarbon abuse has been associated with irregular heart rhythms and

potential cardiac arrest.

**Target Organ Effects** 

Central Nervous System, Respiratory System, Eyes, Skin, Kidney, Blood, Bone Marrow,

and Liver.

**Neurological effects** 

Intentional misuse by deliberately concentrating and inhaling contents may be harmful or

**Aspiration hazard** 

May be fatal if swallowed and enters airways.

### Numerical measures of toxicity - Product Information

0% of the mixture consists of ingredient(s) of unknown toxicity. **Unknown Acute Toxicity** 

The following values are calculated based on chapter 3.1 of the GHS document .

ATEmix (oral) 7028 mg/kg 35727 mg/kg **ATEmix (dermal)** ATEmix (inhalation-gas) 223077 mg/l ATEmix (inhalation-dust/mist) 1.4 mg/l

# 12. ECOLOGICAL INFORMATION

#### **Ecotoxicity**

Chemical Name	Toxicity to algae	Toxicity to fish	Toxicity to	Toxicity to daphnia and
NAPHTHENIC OIL, SEVERLY HYDROT 64742-52-5	-	5000 mg/L LC50 Oncorhynchus mykiss 96h	microorganisms -	other aquatic invertebrates 1000 mg/L EC50 Daphnia magna 48h
TOLUENE 108-88-3	433 mg/L EC50 Pseudokirchneriella subcapitata 96h 12.5 mg/L EC50 Pseudokirchneriella subcapitata 72h static	15.22 - 19.05 mg/L LC50 Pimephales promelas 96h flow-through 12.6 mg/L LC50 Pimephales promelas 96h static 5.89 - 7.81 mg/L LC50 Oncorhynchus mykiss 96h flow-through 14.1 - 17.16 mg/L LC50 Oncorhynchus mykiss 96h static 5.8 mg/L LC50 Oncorhynchus mykiss 96h semi-static 11.0 - 15.0 mg/L LC50 Lepomis macrochirus 96h static 54 mg/L LC50 Oryzias latipes 96h static 28.2 mg/L LC50 Poecilia reticulata 96h semi-static 50.87 - 70.34 mg/L LC50 Poecilia reticulata 96h static		5.46 - 9.83 mg/L EC50 Daphnia magna 48h Static 11.5 mg/L EC50 Daphnia magna 48h

300 - 310	T	I		T = = = = = = = = = = = = = = = = = = =
XYLENE	-	13.4 mg/L LC50 Pimephales	-	3.82 mg/L EC50 water flea
1330-20-7		promelas 96h flow-through		48h 0.6 mg/L LC50
		2.661 - 4.093 mg/L LC50		Gammarus lacustris 48h
		Oncorhynchus mykiss 96h		
		static 13.5 - 17.3 mg/L LC50		
		Oncorhynchus mykiss 96h		
		13.1 - 16.5 mg/L LC50		
		Lepomis macrochirus 96h		
		flow-through 19 mg/L LC50		
		-		
		Lepomis macrochirus 96h		
		7.711 - 9.591 mg/L LC50		
		Lepomis macrochirus 96h		
		static 23.53 - 29.97 mg/L		
		LC50 Pimephales promelas		
		96h static 780 mg/L LC50		
		Cyprinus carpio 96h		
		semi-static 780 mg/L LC50		
		Cyprinus carpio 96h 30.26 -		
		40.75 mg/L LC50 Poecilia		
==:::::::::::::::::::::::::::::::::::::		reticulata 96h static		
ETHYL BENZENE	4.6 mg/L EC50	11.0 - 18.0 mg/L LC50	-	1.8 - 2.4 mg/L EC50
100-41-4	Pseudokirchneriella	Oncorhynchus mykiss 96h		Daphnia magna 48h
	subcapitata 72h 438 mg/L	static 4.2 mg/L LC50		
	EC50 Pseudokirchneriella	Oncorhynchus mykiss 96h		
	subcapitata 96h 2.6 - 11.3	semi-static 7.55 - 11 mg/L		
	mg/L EC50	LC50 Pimephales promelas		
	Pseudokirchneriella	96h flow-through 32 mg/L		
	subcapitata 72h static 1.7 -	LC50 Lepomis macrochirus		
	7.6 mg/L EC50	96h static 9.1 - 15.6 mg/L		
	Pseudokirchneriella	· ·		
		LC50 Pimephales promelas		
	subcapitata 96h static	96h static 9.6 mg/L LC50		
		Poecilia reticulata 96h static		
BENZENE	29 mg/L EC50	10.7 - 14.7 mg/L LC50	-	8.76 - 15.6 mg/L EC50
71-43-2	Pseudokirchneriella	Pimephales promelas 96h		Daphnia magna 48h Static
	subcapitata 72h	flow-through 5.3 mg/L LC50		10 mg/L EC50 Daphnia
		Oncorhynchus mykiss 96h		magna 48h
		flow-through 22.49 mg/L		magna 1011
		LC50 Lepomis macrochirus		
		·		
		96h static 28.6 mg/L LC50		
		Poecilia reticulata 96h static		
		22330 - 41160 µg/L LC50		
		Pimephales promelas 96h		
		static 70000 - 142000 µg/L		
		LC50 Lepomis macrochirus		
		96h static		
NAPHTHALENE	_	5.74 - 6.44 mg/L LC50	-	2.16 mg/L LC50 Daphnia
91-20-3		Pimephales promelas 96h		magna 48h 1.96 mg/L EC50
] 31 20-3		flow-through 1.6 mg/L LC50		Daphnia magna 48h Flow
		Oncorhynchus mykiss 96h		through 1.09 - 3.4 mg/L
		flow-through 0.91 - 2.82		EC50 Daphnia magna 48h
		mg/L LC50 Oncorhynchus		Static
		mykiss 96h static 1.99 mg/L		
		LC50 Pimephales promelas		
		96h static 31.0265 mg/L		
		LC50 Lepomis macrochirus		
		96h static		
<u> </u>	L	J 5 Statio	l .	L

# Persistence and degradability

.

# **Bioaccumulation**

.

Chemical Name	log Pow
DIMETHYLETHER	-0.18
115-10-6	
TOLUENE	2.7
108-88-3	

XYLENE 1330-20-7	2.77 - 3.15
ETHYL BENZENE 100-41-4	3.2
BENZENE 71-43-2	2.1
NAPHTHALENE 91-20-3	3.6

Other adverse effects

No information available

# 13. DISPOSAL CONSIDERATIONS

Waste treatment

Waste Disposal Methods This material, as supplied, is a hazardous waste according to federal regulations (40 CFR

261). Dispose of in accordance with federal, state, and local regulations. This material, as supplied, is a hazardous waste according to federal regulations (40 CFR 261.) Dispose of

in accordance with federal, state, and local regulations.

**Contaminated packaging** Do not re-use empty containers.

# 14. TRANSPORT INFORMATION

DOT Ground CONSUMER COMMODITY ORM-D

or

LIMITED QUANTITY

IATA UN1950, AEROSOLS, FLAMMABLE, 2.1, LTD.QTY.

IMDG UN1950, AEROSOLS, 2.1, LTD. QTY.

# 15. REGULATORY INFORMATION

# **International Inventories**

Chemical Name	TSCA	DSL/NDSL	EINECS/ELI NCS	ENCS	IECSC	KECL	PICCS	AICS
1,1-DIFLUOROETHA NE	Х	Х	Х	Х	Х	Х	Х	Х
NAPHTHENIC OIL, SEVERLY HYDROT	Х	Х	Х	Not listed	Х	Х	Х	Х
DIMETHYLETHER	X	Х	X	Χ	X	Χ	X	X
TOLUENE	Х	Х	Х	Х	Х	Х	Х	Х
METHYLATED SILICA	Х	Х	X	Х	Х	Х	Х	X
XYLENE	Х	Х	Х	Х	Х	Х	Х	Х
ETHYL BENZENE	Х	Х	Х	Х	Х	Х	Х	Х
BENZENE	Х	Х	Х	Х	Х	Х	Х	X
NAPHTHALENE	Х	Х	Х	Х	Х	Х	Х	Х

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

\_\_\_\_\_

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

**ENCS** - Japan Existing and New Chemical Substances

CHINA - China Inventory of Existing Chemical Substances

**KECL** - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

# **U.S. Federal Regulations**

#### **SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does contain a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372:

Chemical Name	CAS-No	Weight %*	SARA 313 - Threshold Values %
TOLUENE - 108-88-3	108-88-3	1-10	1.0
XYLENE - 1330-20-7	1330-20-7	<0.1	1.0
ETHYL BENZENE - 100-41-4	100-41-4	<0.01	0.1
BENZENE - 71-43-2	71-43-2	<0.01	0.1
NAPHTHALENE - 91-20-3	91-20-3	<0.001	0.1

# SARA 311/312 Hazard Categories

Acute Health Hazard	Yes
Chronic Health Star Hazard	Yes
Fire Hazard	Yes
Sudden Release of Pressure Hazard	Yes
Reactive Hazard	No

### **Clean Water Act**

This product does contain the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42):

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
TOLUENE 108-88-3	1000 lb	X	X	Х
XYLENE 1330-20-7	100 lb			Х
ETHYL BENZENE 100-41-4	1000 lb	X	X	Х
BENZENE 71-43-2	10 lb	X	X	Х
NAPHTHALENE 91-20-3	100 lb	X	X	Х

# **CERCLA**

This material, as supplied, does contain substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302):

Chemical Name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ
TOLUENE 108-88-3	1000 lb 1 lb		RQ 1000 lb final RQ RQ 454 kg final RQ RQ 1 lb final RQ RQ 0.454 kg final RQ
XYLENE 1330-20-7	100 lb		RQ 100 lb final RQ RQ 45.4 kg final RQ
ETHYL BENZENE 100-41-4	1000 lb		RQ 1000 lb final RQ RQ 454 kg final RQ
BENZENE 71-43-2	10 lb		RQ 10 lb final RQ RQ 4.54 kg final RQ

NAPHTHALENE	100 lb 1 lb	RQ 100 lb final RQ
91-20-3		RQ 45.4 kg final RQ RQ 1 lb final
		RQ
		RQ 0.454 kg final RQ

# U.S. State Regulations

# **California Proposition 65**

This product contains the following Proposition 65 chemicals: This product does not contain any Proposition 65 chemicals.



This product can expose you to chemicals including those listed below, which is [are] known to the State of California to cause cancer, birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

Chemical Name	California Prop. 65	
TOLUENE - 108-88-3	Developmental 1-10%	
ETHYL BENZENE - 100-41-4	Cancer < 0.01%	
BENZENE - 71-43-2	Cancer /Developmental <0.01%	
NAPHTHALENE - 91-20-3	Cancer < 0.001%	

# U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
1,1-DIFLUOROETHANE 75-37-6	Х	X	
DIMETHYLETHER 115-10-6	Х	X	X
TOLUENE 108-88-3	Х	X	X
XYLENE 1330-20-7	Х	X	X
ETHYL BENZENE 100-41-4	Х	X	X
BENZENE 71-43-2	Х	X	X
NAPHTHALENE 91-20-3	Х	Х	X

EPA Pesticide Registration Number Not applicable

### Canada

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all the information required by the CPR.

# **WHMIS Hazard Class**

B5 Flammable aerosol A Compressed gases D2B Toxic materials

# **16. OTHER INFORMATION**

NFPA	Health Hazard 2	Flammability 4	Instability 0	Physical and chemical
MITA_	House Hazara Z	1 Idillillability	motubility 0	hazards -
HMIS	Health Hazard 2*	Flammability 4	Physical Hazard 1	Personal protection B

Issuing date 14-Mar-2017 Revision Date 28-Mar-2018 Revision Note

# Disclaimer

The information provided on this SDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

**End of Safety Data Sheet**