

CLASSIC SERIES MODELS

**LIKE NEW
RENTALS**



**SALE
PRICES**



SPECIFICATIONS

| CLASSIC SERIES | | Model Name | Classic 18 | Classic Plus 26 | |
|---|----------------------------|----------------------|-------------------|--------------------|-----|
| | | Part Number | 15SFU-1 | 24HFU-1 | |
| COOLING CAPACITY (Btu/h) Rating conditions: 95°F at 60% RH. | | | 18,000 | 26,000 | |
| ELECTRICAL CHARACTERISTICS | Power Supply (Volts) | | 1 Phase, 208/230V | 1 Phase, 208/230V | |
| | Power Consumption (kW) | | 2.1 | 2.8 | |
| | Current Consumption (Amps) | | 10.8/10.0 | 13.8/12.8 | |
| | Fuse Size (Amps) | | 20 | 20 | |
| | NEMA Plug Configuration | | 6-15 | L6-20 | |
| | Min-Max Voltage | | 195-250 | 195-250 | |
| FANS | Evaporator | Fan Type | Centrifugal | Centrifugal | |
| | | Max Air Flow (CFM) | 530 | 708 | |
| | | Max Ext Static (IWG) | .52 | .54 | |
| | Motor Output (kW) | | | .35 | .46 |
| | Condenser | Fan Type | Centrifugal | Centrifugal | |
| | | Air Flow (CFM) | 1177 | 1680 | |
| Max Ext Static (IWG) | | .25 | .25 | | |
| COMPRESSOR | Type | Hermetic Rotary | Hermetic Rotary | | |
| | Output (kW) | 1.1 | 1.5 | | |
| R-22 Charge (lbs.) | | | 1.59 | 2.3 | |
| Dimensions W x D x H (inches) | | | 19.3 x 26.4 x 41 | 19.3 x 28.7 x 46.9 | |
| Weight (lbs.) | | | 167 | 220 | |
| Power Cord | Gauge (AWG) | | 14 (3 core) | 14 (3 core) | |
| | Length (ft.) | | 6 | 6 | |
| Condensate Tank Capacity (gal.) Pump Kit Available | | | 5.3 | 5.3 | |
| Operating Conditions Min-Max (°F at 50% RH) | | | 68° -104° | 70° -115° | |
| Maximum Length - Per Cold Duct Hose | | | 50' | 50' | |
| Maximum Length - Hot Duct Hose | | | 80' | 45' | |
| Max Sound Level (dB) | With Condenser Duct | | 63 | 66 | |
| | Without Condenser Duct | | 67 | 69 | |
| PRICES | Part Number | | 15SFU-1 | 24HFU-1 | |
| | LIST PRICE | | \$2995.00 | \$3875.00 | |
| | SALE PRICE | | \$1995.00 | SOLD OUT | |

| ELECTRICAL FUNCTIONS | 15SFU-1 | 24HFU-1 |
|-----------------------------------|------------|---------|
| Compressor Overload Relay | • | • |
| Fan Motor Protection | • | • |
| Anti-Freezing Thermostat | • | • |
| Thermostat Type | Mechanical | Digital |
| Automatic Full Tank Shut-Off | • | • |
| High Pressure Switch | • | • |
| Compressor Short-Cycle Protection | • | • |
| Return Air Thermostat | • | • |
| Automatic Restart | • | • |
| Accommodates Condensate Pump Kit | • | • |

All specifications subject to change without notice. All models are UL Listed. Standard warranty includes 12 months on entire unit and 36 months on the compressor.



PLASTIC PROCESS EQUIPMENT, INC.

www.ppe.com • e-mail: sales@ppe.com

6385 Montessouri Street, Las Vegas, Nevada 89113
702-433-6385 • 800-258-8877 • Fax: 702-433-6388

11218 Challenger Avenue, Odessa, Florida 33556
727-834-8888 • 800-282-6783 • Fax: 727-834-8873

8303 CORPORATE PARK DRIVE, MACEDONIA (Cleveland), OHIO 44056, USA

216-367-7000 • Toll Free: 800-321-0562 • Fax: 216-367-7022 • Order Fax: 800-223-8305

Toll Free: USA, Canada & Mexico
800-362-0706