STAINLESS STEEL VACUUM HOPPER LOADERS

SPECIFICATION COMPARISON CHART

4 MODELS






	MODELS			
FEATURES	**TAL-15UFXDS**	**TAL-6UFX**	**TAL-12UFXDS**	**TAL-3U-EFXDS**
LBS Per Hour*	450	660	900	450
Motor H.P.	1.5	1.5	1.5	1.5
Proportional Loading	Available	Available	Available	Available
Filter Blow-Off	Yes	Yes	Yes	Yes
Microprocessor Control	Yes	Yes	Yes	Yes
Remote Control Pad	Yes	Yes	Yes	Yes
Loader Construction	Stainless Steel	Stainless Steel	Stainless Steel	Stainless Steel
Hopper Capacity (polypro)	3.5 lbs.	8.5 lbs.	17 lbs.	4.5 lbs.
Function Lights	Yes	Yes	Yes	Yes
On Demand Cycle Control	Yes	Yes	Yes	Yes
Filter Diameter	7-5/8" O.D.	9-1/2" O.D.	12-1/2" O.D.	7-5/8" O.D.
Filter Material	Reinforced Cloth	Reinforced Cloth	Reinforced Cloth	Reinforced Cloth
Vacuum Hose Grounded	Yes	Yes	Yes	Yes
Hose Length	10 ft.	10 ft.	10 ft.	10 ft.
Probe Part No.	TALP36	TALP36	TALP36	TALP36
Hose/Probe Diameter	1-1/2"	1-1/2"	1-1/2"	1-1/2"
Probe Length	36"	36"	36"	36"
Discharge Hole Dia.	6"	8-1/4"	8-1/4"	2-1/4"
Height above Hopper	22-1/2"	26-3/4"	24-1/2"	28-1/8"
Weight (empty)	25 lbs.	29 lbs.	30-1/2 lbs.	29 lbs.
PRICE	**$950.00**	**$1,080.00**	**$1,360.00**	**$1,425.00**

* Tested with virgin Polypro beads at 10ft vertical and 10ft horizontal transport. Do not use with powders.



SEE BEYOND FOR PROBES.

PLASTIC PROCESS EQUIPMENT, INC.

EAST: 8303 CORPORATE PARK DRIVE, MACEDONIA, OHIO 44056-2300, 216-367-7000 • FAX: 216-367-7022, TOLL FREE: 800-321-0562

WEST: 6385 MONTESSOURI STREET, LAS VEGAS, NEVADA 89113-1186, 702-433-6385 • FAX: 702-433-6388, TOLL FREE: 800-258-8877

www.ppe.com
e-mail: sales@ppe.com
Toll Free: USA, Canada & Mexico
800-362-0706
Order Fax: 800-223-8305