



# HONEYCOMB DESICCANT ROTOR DRYERS

THE LATEST HONEYCOMB MATRIX DESICCANT ROTOR WHEEL TECHNOLOGY

**NO PEAKS  
AND VALLEYS**

**MAX-DRY® =  
CURRENT STATE OF THE ART DRYING**



**TYPICAL APPLICATION**



**STAINLESS STEEL AIR CONE**  
13-7/8" Long X  
7-7/8" O.D. X  
2" O.D. Tube  
CP-CN1  
\$95.00



**RELIABLE  
AFFORDABLE  
CONTINUOUS DRY AIR**

**Drying Rates\***

RESIN TYPE	DRYING TEMPERATURE		DRYING TIME HOURS	DRYING RATES LBS. PER HOUR				
	°C	°F		FX-050	FX-100	FX-180	FX-300	FX-400
ABS	80	176	3 - 4	65	132	220	365	485
POM	100	212	2	65	132	230	400	530
PMMA	80	176	2 - 3	65	132	230	385	510
NYLON	75	168	4 - 6	55	110	200	330	440
PC	120	248	3 - 4	55	100	165	285	375
PU	90	194	2 - 3	55	100	165	285	375
PBT	130	267	3 - 4	45	80	132	220	300
PE	90	194	1	45	90	165	265	355
PET	160	320	4 - 6	45	80	132	220	300
PPO	110	230	2	55	100	175	300	400
PP	90	194	1	55	100	175	300	400
PS	80	176	1	65	132	230	400	530
PSU	120	248	3 - 4	55	100	175	300	400
PVC	70	158	1	90	165	300	495	650

\* Times and temperatures are general guidelines. Information on specific resins should be obtained from resin suppliers. Maximum drying temperature is 400°F.



**PLASTIC PROCESS EQUIPMENT, INC.**  
**EAST** 8303 CORPORATE PARK DRIVE  
 MACEDONIA, OHIO 44056-2300  
 216-367-7000 • FAX: 216-367-7022  
 TOLL FREE: 800-321-0562

**WEST** 6385 MONTESSOURI STREET  
 LAS VEGAS, NEVADA 89113-1186  
 702-433-6385 • FAX: 702-433-6388  
 TOLL FREE: 800-258-8877

**www.ppe.com**  
 e-mail: sales@ppe.com  
**Toll Free: USA, Canada & Mexico**  
**800-362-0706**  
 Order Fax: 800-223-8305