



# OXISHIELD CORROSION INHIBITOR

## STOPS CORROSION, OXIDATION AND SCALE BUILD-UP.



**Untreated System**



**USE WITH WATER OR GLYCOL**



**Treated System**

OXISHIELD CORROSION INHIBITOR is specifically designed to control corrosion in systems circulating fluid to industrial machines. OxiShield is very effective as a corrosion inhibitor where copper, aluminum, tin, ferrous metals, lead and/or brass and other yellow metals are present in a closed circuit heating/cooling system. It prevents galvanic action from occurring if some or all of the above dissimilar metals are in the system. It also prevents oxidation or rusting of the ferrous metals in the system.



Filters must be used in systems with OxiShield, especially on existing systems where scale and/or other corrosion contaminants have built up. OxiShield will free and clean off some or all of this scale and/or corrosion. Install filters on the return side of the system to protect pumps, seals and other components! OxiShield is normally used diluted 10:1. It is recommended that deionized or distilled water be used with OxiShield. OxiShield is also effective as a corrosion inhibitor in water or uninhibited glycol solutions.

### OxiShield Prices (UNDILUTED)

PART NO.	CONTAINER SIZE	QUANTITY PRICES	
		1 - 4	5+
CP01	1 GALLON	\$50.00	\$47.00
CP05	5 GALLON	\$200.00	\$190.00
CP55	55 GALLON	\$1,850.00	

INSTRUCTIONS INCLUDED

### — COLD WATER FILTER —

Designed for 100 PSI & 100°F Max  
1" NPT Inlet & Outlet, Max GPM = 20  
Outside Dimension: 13-1/2" H x 7-1/4" Dia.  
(cartridge not included - see Accessories below)

#### FILTER HOUSING

#WSF10 ..... \$47.65 ea.

#### ACCESSORIES

30 Micron Cartridge  
Pleated Polyester - Reuseable —  
#RF1030 ..... \$23.95 ea.  
Mounting Bracket with screws  
#WBK10 ..... \$50.20 ea.  
Spanner Wrench  
#SW-3 ..... \$5.45 ea.



4-1/2" dia.  
10" long

### — HOT WATER FILTER —

#### 304 STAINLESS STEEL HIGH PRESSURE

Designed for 250 PSI & 250°F Max  
3/4" NPT Inlet & Outlet, Max GPM = 10  
Outside Dimension: 14" H x 4" Dia.  
(cartridge not included - see Accessories below)

#### FILTER HOUSING

#WSFSS-1 ..... \$310.60 ea.

#### ACCESSORIES

25 Micron Cartridge (40 - 175°F) —  
#155749-43 ..... \$7.85 ea.  
50 Micron Cartridge (40 - 175°F) —  
#155752-43 ..... \$7.10 ea.  
Mounting Bracket with screws  
#WBKSS-1 ..... \$29.20 ea.

Higher flow units available to order.



2-1/2" dia.  
9-3/4" long



## PLASTIC PROCESS EQUIPMENT, INC.

8303 CORPORATE PARK DRIVE  
MACEDONIA, OHIO 44056-2300  
216-367-7000 • FAX: 216-367-7022  
TOLL FREE: 800-321-0562

6385 MONTESSOURI STREET  
LAS VEGAS, NEVADA 89113-1186  
702-433-6385 • FAX: 702-433-6388  
TOLL FREE: 800-258-8877

www.ppe.com  
e-mail: sales@ppe.com

Toll Free: USA, Canada & Mexico  
**800-362-0706**

Order Fax: 800-223-8305