



NYLON RECOIL AIR HOSE

360° SWIVEL FITTING AT ONE END



Gives extra protection along with spring guards against hose end damage.
Facilitates hookup and disconnection and provides free tool action by eliminating hose twisting.

SPECIFICATIONS

- Less than 1% moisture absorption. (nylon 12)
- Resistant to most chemicals, including alkalis, hydrocarbons, ketones and esters.
- Abrasion resistant.
- 260 PSI working pressure.
- Temperature Range: -14° to +170°F.
- Color may vary.
- Suggested working length for most applications, is 80% for vertical use and 50% for horizontal use (such as cranes, monorails, trolleys, etc.).



TIGHT COIL CONFIGURATION

The smaller diameter eliminates unhandy bulkiness, prevents end-looping and increases retractability. Keeps hose out of the way.

PART NO.	HOSE I.D. (INCHES)	HOSE LENGTH (FEET)	MALE NPT SWIVEL FTG EACH END	COMPACT LENGTH (INCHES)	PRICE EACH
14251	1/4"	25'	1/4"	12"	\$18.50
14501	1/4"	50'	1/4"	23"	\$26.25
16121	3/8"	12'	3/8"	5"	\$22.85
16251	3/8"	25'	3/8"	10"	\$39.15
16501	3/8"	50'	3/8"	20"	\$69.50
17121	1/2"	12'	1/2"	5"	\$20.00
17501	1/2"	50'	1/2"	18"	\$36.00



4" ANGLED TIP BLOW GUN WITH CONTOURED HANDLE

FEATURES

- Insulated fiberglass reinforced nylon grip.
- Contoured handle for better handling.
- 4" long barrel angled at 15°.
- Brass air flow valve.

SPECIFICATIONS

Air Pressure 90 P.S.I.
Air Consumption 11 C.F.M.
Air Inlet 1/4" N.P.T.



PART NO. M687
PRICE
\$5.15

ALWAYS: Always use safety eyewear.

This is not a safety blow gun and does not have a safety bypass to prevent tip pressure build up in the event of tip blockage. This product is designed for compressed air lines only. Do not use this blow gun on air lines that are not regulated unless you are permitted to do so.



PLASTIC PROCESS EQUIPMENT, INC.

8303 CORPORATE PARK DRIVE
MACEDONIA, OHIO 44056-2300
216-367-7000 • FAX: 216-367-7022
TOLL FREE: 800-321-0562

6385 MONTESSOURI STREET
LAS VEGAS, NEVADA 89113-1186
702-433-6385 • FAX: 702-433-6388
TOLL FREE: 800-258-8877

www.ppe.com
e-mail: sales@ppe.com

Toll Free: USA, Canada & Mexico
800-362-0706

Order Fax: 800-223-8305