



MINI BRASS BALL VALVES

CHROME PLATED

ISO-9002

MANUFACTURED IN A
QUALITY SYSTEM CERTIFIED
FACILITY.



PPE industrial quality, one piece brass bar stock design Mini Brass Ball Valves provide the space savings necessary for small line fluid control applications. Designed for handling compressed air, water, fuels, gases, and other non-corrosive liquids in industrial applications that require compact ball valves. Top-of-the-line features include 235psi MWP Rating, PTFE ball seats for a positive seal in both directions, Viton stem seal, chrome plated brass ball and body for long life and extra corrosion resistance, bottom loaded stem for safety. Corrosion resistant nylon wing handle is compact, easy to use, and clearly shows ball position. Each valve is leak tested to ensure quality. Valve body functions as wrench flats for easy installation.



FEMALE X FEMALE



MALE X FEMALE

FEMALE X FEMALE

Part No.	Thread Size N.P.T.	QUANTITY PRICES	
		1-9	10+
FMV-0018	1/8"	\$5.31	\$5.03
FMV-0014	1/4"	\$5.75	\$5.46
FMV-0038	3/8"	\$5.75	\$5.46
FMV-0012	1/2"	\$5.98	\$5.68

MALE X FEMALE

MMV-0218	1/8"	\$4.87	\$4.63
MMV-0214	1/4"	\$6.06	\$5.77
MMV-0238	3/8"	\$6.04	\$5.75
MMV-0212	1/2"	\$7.07	\$6.72

- Temp Range: 32°F to 176°F
- Threads: Full N.P.T. made to ANSI standards B1.20.1
- Porting: Full on 1/8" & 1/4" sizes
Standard on 3/8" & 1/2" sizes
- Ball Seats: PTFE
- Body: Chrome plated brass hex, one piece forged
- Ball: Chrome plated brass
- Blowout-proof brass stem.
- Stem Seal: Viton
- MWP Rating: 235psi, will handle 300psi @ 75°F
- Handle: Nylon - corrosion resistant
- Each valve is seal tested for safety.
- Double seal system for operation in both directions.
- 1/4 turn handle with mechanical stop.



BRASS MINI-BALL VALVES

WITH STANDARD BARBED INSERT

- Temp Range: 14°F to 212°F
- Threads: 1/8" & 1/4" N.P.T.
- 180° Operational 1/4 turn handle with mechanical stop.
- Standard Porting.

- Double seal system for operation in both directions.
- Blowout-proof brass stem.
- 200 WOG rating.
- 125 WSP rating.


- Body: Forged Brass
- Ball: Chrome plated brass
- Ball Seats: PTFE
- Handle: Steel with PVC cover.
- O-Ring: NBR



ISO-9002
MANUFACTURED IN A
QUALITY SYSTEM CERTIFIED
FACILITY.



**GREAT QUALITY!
GREAT PRICE!**



MALE X HOSE BARB

PART NO.	THREAD SIZE	HOSE I.D.	PRICES	
			1-9	10+
944-138	1/4" NPT	1/4"	\$3.06	\$2.92
944-128	1/4" NPT	3/8"	\$3.12	\$2.96

HOSE BARB X HOSE BARB

PART NO.	BARB HOSE I.D.	PRICES	
		1-9	10+
944-142	1/4" 1/4"	\$2.68	\$2.54
944-134	3/8" 3/8"	\$3.10	\$2.96

FEMALE X HOSE BARB

PART NO.	THREAD SIZE	HOSE I.D.	PRICES	
			1-9	10+
944-135	1/8" NPT	1/8"	\$3.65	\$3.50
944-121	1/4" NPT	5/16"	\$3.11	\$2.96
944-136	1/4" NPT	1/4"	\$2.58	\$2.45



PLASTIC PROCESS EQUIPMENT, INC.

8303 CORPORATE PARK DRIVE
MACEDONIA, OHIO 44056-2300
216-367-7000 • FAX: 216-367-7022
TOLL FREE: 800-321-0562

6385 MONTESSOURI STREET
LAS VEGAS, NEVADA 89113-1186
702-433-6385 • FAX: 702-433-6388
TOLL FREE: 800-258-8877

www.ppe.com
e-mail: sales@ppe.com

Toll Free: USA, Canada & Mexico
800-362-0706

Order Fax: 800-223-8305