



HI-HEAT FIBERGLASS ELECTRICAL TAPE



PPE Hi-Heat Fiberglass cloth adhesive back tape is ideal for high temperature applications such as heater bands, cartridge heaters, etc. The dielectric strength rating is 2500 volts with a temperature rating of -100°F to +500°F.

| PART NO. | DESCRIPTION | PRICE |
|----------|----------------|-------------|
| HFT-35 | 1/4" x 108 ft. | \$10.75 ea. |
| HFT-36 | 1/2" x 108 ft. | \$17.25 ea. |
| HFT-37 | 3/4" x 108 ft. | \$25.25 ea. |



HI-HEAT GLASS CLOTH TAPE BY 3M

3M Hi-Heat Electrical Tapes are ideal for use on heater bands and thermocouple lead extensions as well as all high heat applications. We offer two temperature ratings and mil thicknesses. Both are thermosetting with pressure sensitive adhesive for a long service life.

27 GLASS CLOTH ELECTRICAL TAPE

- Operates at 266°F (130°C)
- 7 mil thickness
- UL recognized component listing for 150°C (Guide OANZ2, File E17385). CSA accepted component 130°C file LR93411. Meets MIL-I-15126F type GFT.



2 TYPES



69 GLASS CLOTH ELECTRICAL TAPE

- Operates at 356°F (180°C)
- 7.5 mil thickness
- Meets requirements of MIL-I-19166C and has UL recognized component listing for 200°C (Guide OANZ2, file E17385). CSA accepted component 180°C file LR93411.

| PART NO. | SIZE | TEMP RANGE | THICKNESS | PRICE |
|----------|---------------|-------------|-----------|-------------|
| 275066 | 1/2" x 66 ft. | 266°F/130°C | 7 Mil | \$18.90 ea. |
| 277566 | 3/4" x 66 ft. | 266°F/130°C | 7 Mil | \$25.75 ea. |
| 695066 | 1/2" x 66 ft. | 356°F/180°C | 7.5 Mil | \$21.50 ea. |
| 697566 | 3/4" x 66 ft. | 356°F/180°C | 7.5 Mil | \$31.50 ea. |



GENERAL PURPOSE DUCT TAPE

A VERSATILE GENERAL PURPOSE POLY-COATED CLOTH-BACKED DUCT TAPE



NC203 Cloth-Backed Duct Tape is laminated to a tightly woven cloth scrim with a layer of polyethylene coated cloth and then coated with an aggressive rubber-based adhesive.

Beware of Cheap Vinyl Imitations!

FOR USE ON:

- HVAC duct sealing.
- Air conditioning duct sealing.
- Military specification packaging.
- Sound dampening.
- Splicing.
- High pressure sand blasting.
- Apollo 13

FEATURES:

- COLOR: Gray
- SIZE: 2" x 180' (60 yds.)
- Standard Grade (9.0 Mil thick)
- Excellent adhesion to a wide variety of surfaces.
- Rubber-based adhesive
- Extra Holding Power
- 1,001 uses!
- Max. Temp Range 200°F
- Low VOC Content <1 g/L

| PART NO. | QUANTITY PRICING | |
|----------|------------------|------------|
| | 1-5 ROLLS | 6+ ROLLS |
| NC203 | \$9.80 ea. | \$9.30 ea. |



PLASTIC PROCESS EQUIPMENT, INC.

8303 CORPORATE PARK DRIVE
 MACEDONIA, OHIO 44056-2300
 216-367-7000 • FAX: 216-367-7022
 TOLL FREE: 800-321-0562

6385 MONTESSOURI STREET
 LAS VEGAS, NEVADA 89113-1186
 702-433-6385 • FAX: 702-433-6388
 TOLL FREE: 800-258-8877

www.ppe.com
 e-mail: sales@ppe.com

Toll Free: USA, Canada & Mexico
800-362-0706

Order Fax: 800-223-8305