




HEATER BAND WIRING

2 PIECE HEATER BANDS




120 VOLTS PER HALF

2 PIECE BAND RATED 240 VOLTS 1,000 WATTS. EACH HALF IS 120 VOLTS 500 WATTS. WIRE EACH HALF IN PARALLEL.




2 PIECE BAND RATED 240 VOLTS 1,000 WATTS. EACH HALF IS 120 VOLTS 500 WATTS. WIRE EACH HALF IN SERIES.




240 VOLTS PER HALF

2 PIECE BAND RATED 480 VOLTS 1,000 WATTS. EACH HALF IS 240 VOLTS 500 WATTS. WIRE EACH HALF IN PARALLEL.




2 PIECE BAND RATED 480 VOLTS 1,000 WATTS. EACH HALF IS 240 VOLTS 500 WATTS. WIRE EACH HALF IN SERIES.




PARALLEL WIRING:

120 VOLT PER HALF WIRED 120 VOLT




SERIES WIRING:


120 VOLT PER HALF WIRED 240 VOLT



240 VOLT PER HALF WIRED 240 VOLT



240 VOLT PER HALF WIRED 480 VOLT



CAUTION: START-UP

Due to moisture contained especially in new heater bands we suggest using a soft start program. This allows the moisture to dissipate gradually limiting ground fault current to a reduced value.

© Copyright 2022 Plastic Process Equipment, Inc. Note: PPE customers may reproduce this form only in its entirety.



PLASTIC PROCESS EQUIPMENT, INC.

EAST 8303 CORPORATE PARK DRIVE
MACEDONIA, OHIO 44056-2300
216-367-7000 • FAX: 216-367-7022
TOLL FREE: 800-321-0562

WEST 6385 MONTESSOURI STREET
LAS VEGAS, NEVADA 89113-1186
702-433-6385 • FAX: 702-433-6388
TOLL FREE: 800-258-8877

www.ppe.com

e-mail: sales@ppe.com

Toll Free: USA, Canada & Mexico

800-362-0706

Order Fax: 800-223-8305