TIE BAR STRAIN GAUGES

HELPS ELIMINATE TIE BAR BREAKAGE

DISCONTINUED AND OUT OF STOCK

FEATURES

- Helps Eliminate tie bar breakage, die splitting, and toggle pin wear.
- Simple to use.
- Adjust machine for maximum tonnage.
- Attaches with lever-engaged magnetic clamps.
- Two piece design eliminates alignment problems.
- Move from tie bar to tie bar quickly.
- Includes hardened steel anvils.
- Zeroing lever for calibration.
- NIST certification.
- Complete instructions included.

SPECIFICATIONS

- Accuracy:
  - DA - ± 500psi @ 10,000psi
  - DSA - ± 500psi @ 10,000psi
- Designed for machines with 10,000 psi on the bar. Mathematical correction factor required for other types.

This unique Tie Bar Strain Gauge helps eliminate tie bar breakage, die splitting, and toggle pin wear by enabling you to adjust your machine for maximum tonnage. It also allows setting tie bars for equal pickup at reduced tonnage. Ideal for large die casting machines and multiple cavity molds. Gauges mount magnetically off and on.

Simple to operate, the DSA Strain Gauge attached with lever-engaged magnetic clamps and provides a direct readout of tie bar tension in pounds per square inch. The Tie Bar Strain Gauge can be used to adjust two and four post trim press locking wedges.

The Tie Bar Strain Gauges are available in 3 models, 2 analog and 1 digital. The DA models are a two-piece system which makes alignment problems a thing of the past. They are used on tie bars of 2" diameter or greater where there is 14" of clear space for taking readings. The DSA model is shorter requiring just 8" of tie bar and can be used on tie bar diameters as small as 1-3/4". The DA model is also available with a digital readout which can provide remote access to the readings.

DA MODELS

FOR 100+ TON MACHINES

Requires 14" clear bar space

Will fit 2" dia. or larger tie bars

1 YEAR WARRANTY



Stock Analog Model shown.

Wooden Case included.

Analog Model **DA10001**

Price **$1,603.80**

Digital Model **DA10003**

This model uses a Mitutoyo 543-793B Absolute Digimatic Indicator.



Price **$2,643.00**

DSA MODEL

FOR 25-100 TON MACHINES

Requires 8" clear bar space

Will fit 1-3/4" to 6" dia. tie bars



Stock Analog Model shown.

Analog Model **DSA10015**

Price **$1,730.00**

Complete repair service available, cost = time & materials.

Factory Recalibration available **$330.50**

PLASTIC PROCESS EQUIPMENT, INC.

EAST: 8303 CORPORATE PARK DRIVE, MACEDONIA, OHIO 44056-2300, 216-367-7000 • FAX: 216-367-7022, TOLL FREE: 800-321-0562

WEST: 6385 MONTESSOURI STREET, LAS VEGAS, NEVADA 89113-1186, 702-433-6385 • FAX: 702-433-6388, TOLL FREE: 800-258-8877

www.ppe.com

e-mail: sales@ppe.com

Toll Free: USA, Canada & Mexico

800-362-0706

Order Fax: 800-223-8305